

FLOOR



FLOOR

FIELD TILES	
SIZE	THICKNESS*
GLAZED PORCELAIN TILES	
Square 7.4"x7.4"	0.236" (6mm)
Picket 1.5"x9"	0.236" (6mm)
Hex 8"x9"	0.275" (7mm)
Hex Deco 8"x9"	0.275" (7mm)
RECYCLED GLASS	
Vintage Hex 1" 11.85"x11.41"	0.173" (4.4mm)
Vintage Hex 1" Flower 11.85"x9.13"	0.173" (4.4mm)

APPLICATIONS				
	SUITABLE RESIDENTIAL		SUITABLE COMMERCIAL	
	GLAZED PORCELAIN TILES	RECYCLED GLASS	GLAZED PORCELAIN TILES	RECYCLED GLASS
Bathroom Walls	YES	YES	YES	YES
Shower Walls	YES	YES	YES	YES
Kitchen Walls	YES	YES	YES	YES
Countertops	YES	YES	NO	NO
Fireplace Surrounds	YES	YES	YES	YES
Outdoor Cooking / Bar Spaces	YES	YES	YES	YES
Pool Waterlines / Water Fountains	NO	YES	NO	YES
Floors	YES	YES	NO	NO

PERFORMANCE CHARACTERISTICS			
	TEST METHOD ATSM / ISO	RESULT	
		GLAZED PORCELAIN TILES	RECYCLED GLASS
Target DCOF * >.42Wet	ANSI A137-2012	>0.50	>0.42
PEI Rating	ANSI A137.1-2008 UNE EN ISO 10545-7	White	4
		Bone	3
		Light Gray	3
		Dark Gray	3
		Azure	3
		Black	2
		Wood	3
		Deco	3
Moisture Absorption	ASTM C-373 UNE EN ISO 10545-3	≤ 0.50%*	< 0.50%
Break Strength	ASTM C-648 UNE EN ISO 10545-4	Pass	Pass
Chemical Resistance to Staining	ASTM C-650 UNE EN ISO 10545-14	Resistant	Resistant
Freeze-Thaw Resistance	ASTM C-1026 UNE EN ISO 10545-12	Yes	Yes

INSTALLATION		
GROUT JOINT RECOMMENDATION	SHADE VARIATION	
	GLAZED PORCELAIN TILES	RECYCLED GLASS
Minimum of 5/64"	V1 - Uniform Appearance	V2 - Slight Variation

CLEANING RECOMMENDATIONS
Routine with a non-abrasive/non-acidic, mild and PH neutral cleaner

CHARACTERISTICS		
	GLAZED PORCELAIN TILES	RECYCLED GLASS
Glaze	Solid	Solid
Surface Sheen	Semi-Matte	Semi-Matte
Texture	Smooth	Slightly Undulated

*Thickness is understood as the highest point of the tile.

Due to the nature of our tile, a certain amount of variation in color, shading, surface and texture are to be expected.