

Oetiker Stainless Steel PEX Clamp

Job Name _____
 Location _____
 Engineer _____
 Contractor _____
 Tag _____ PO# _____

Specifications

Manufactured to the highest industry standards, StepLess® PEXGrip® Pro Clamps provide precise, leak-free connections. The patented PEXGrip® design prevents the clamp from sliding and provides a 360-degree seal. The new design features a wider band that aids in clamp placement, resulting in easier installation. Approved for use with PEX-B piping and F1807 crimp fittings. Can also be used with PEX-A piping.

Applications

Oetiker Stainless Steel PEX Clamps are approved for use with commercial and residential water applications.

Materials

Stainless Steel

Dimensions and Product Offering

PART NO.	SIZE	A - IN (MM)	A TOLERANCE ±IN(MM)	B - IN (MM)	B TOLERANCE ±IN(MM)	C - IN (MM)	C TOLERANCE ±IN(MM)	WEIGHT - LBS (G)	WEIGHT TOLERANCE ±LBS (G)
C76170	3/8"	0.51 (12.95)	(+.015-.004) ((+.4-.1))	0.35 (9.00)	(+.015-.004) ((+.4-.1))	0.02 (0.60)	0.004 (0.10)	0.01 (4.54)	0.001 (0.45)
C76171	1/2"	0.62 (15.80)	(+.015-.004) ((+.4-.1))	0.35 (9.00)	(+.015-.004) ((+.4-.1))	0.02 (0.60)	0.004 (0.10)	0.01 (4.54)	0.001 (0.45)
C76172	3/4"	0.89 (22.50)	(+.015-.004) ((+.4-.1))	0.35 (9.00)	(+.015-.004) ((+.4-.1))	0.03 (.80)	0.004 (0.10)	0.02 (9.07)	0.001 (0.45)
C76173	1"	1.13 (28.75)	(+.015-.004) ((+.4-.1))	0.39 (10.00)	(+.015-.004) ((+.4-.1))	0.04 (1.00)	0.004 (0.10)	0.02 (9.07)	0.001 (0.45)

Certifications and Approvals

Compliant with ASTM 2098, ASTM F877, and CSA B137.5

