

MIC® Tight-Buffered, Interlocking Armored Cable, Plenum 12 F, 62.5 μm multimode (OM1)



Part Number:
012K88-33130-A3

Corning MIC® interlocking armored plenum cables are designed for use in plenum, riser and general purpose environments for intrabuilding backbone and horizontal installations. These multifiber cables use individually jacketed 900 μm buffered fibers enabling easy, consistent stripping and facilitating termination. The fibers are grouped into jacketed subunits and surrounded by a dielectric central member. The core is protected by a flexible, spirally wrapped, aluminum interlocking armor that offers easy, one-step installation and up to seven times the crush protection of unarmored cables. With a flame-retardant outer jacket, this cable is particularly useful for heavy traffic or more challenging mechanical exposure conditions and applications requiring extra rugged cables.

Features and Benefits

Flexible, interlocking armor design


Seven times crush protection compared to non-armored cables

TBII buffered fibers


Easy, consistent stripping

Flame-retardant jacket

Rugged and durable



MIC® Tight-Buffered, Interlocking Armored Cable, Plenum, 12 F, 62.5 μm multimode (OM1)



MIC® Tight-Buffered, Interlocking Armored Cable, Plenum, 12 F, 62.5 μm multimode (OM1)

MIC® Tight-Buffered, Interlocking Armored Cable, Plenum 12 F, 62.5 µm multimode (OM1)



Specifications

General Specifications	
Cable Type	Tight-Buffered
Environment	Indoor
Product Type	Interlocking Armor
Fiber Category	62.5 µm MM (OM1)
Flame Rating	Plenum (OFCP)
Application	General purpose, Horizontal, Plenum, Vertical Riser
Cable geometry	Round

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	National Electrical Code® (NEC®) OFCP, NFPA 262, CSA FT-6
Design and Test Criteria	ICEA S-83-596

Environmental Conditions	
Temperature Range, Installation	0 °C to 60 °C (32 °F to 140 °F)
Temperature Range, Operation	0 °C to 70 °C (32 °F to 158 °F)
Temperature Range, Storage	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design	
Central Element	Yarn
Fiber Count	12
Number of Ripcords	2
Outer Jacket Color	Orange
Outer Jacket Material	Flame-retardant
Tensile Strength Elements and/or Armoring - Layer 1	Dielectric strength members

MIC® Tight-Buffered, Interlocking Armored Cable, Plenum 12 F, 62.5 μm multimode (OM1)



Cable Design	
Tensile Strength Elements and/or Armoring - Layer 2	Dielectric strength members
Inner Jacket Material	Flame-retardant
Tight Buffer Color, Layer 2	Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Flame Rating	Plenum (OFCP)

Mechanical Specifications	
Max. Tensile Strength, Long-Term, ≤12F	132 N (29.67 lbf)
Max. Tensile Strength, Long-Term, >12F	200 N (44.96 lbf)
Max. Tensile Strength, Long-Term	132 N (29.67 lbf)
Max. Tensile Strength, Short-Term, ≤12F	440 N (98.92 lbf)
Max. Tensile Strength, Short-Term, >12F	660 N (148.37 lbf)
Max. Tensile Strength, Short-Term	440 N (98.92 lbf)
Min. Bend Radius Installation	170 mm (6.69 in)
Min. Bend Radius Operation	113 mm (4.45 in)
Nominal Inner Cable Diameter	6 mm (0.24 in)
Nominal Outer Diameter	11.43 mm (0.45 in)

Optical Characteristics	
Fiber Code	K
Fiber Name	62.5 μm MM (OM1)
Fiber Type	Multimode
Performance Option Code	30
Fiber Core Diameter	62.5 μm
Minimum Effective Modal Bandwidth (EMB)	220 MHz
Maximum Attenuation	3.4 dB/km / 1.0 dB/km
Min. Overfilled Launch (OFL) Bandwidth	200 MHz / 500 MHz
Serial 1 Gigabit Ethernet	300 m / 550 m
Serial 10 Gigabit Ethernet	33 m / -

MIC® Tight-Buffered, Interlocking Armored Cable, Plenum 12 F, 62.5 µm multimode (OM1)



Optical Characteristics	
Wavelengths	850 nm / 1300 nm
Fiber Category	OM1

Dimensions	
Cable Weight	113 kg/km (75.93 lb/1000 ft)
Length	0 mm (0 in)



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.