

CRC 6-56® Multi-Purpose Lubricant



Product Description

Take on the harshest conditions with 6-56®. This superior lubricant resists water and salt spray, driving out moisture that can cause electrical failures and hard starts. Its powerful formula penetrates deep through rust and corrosion to free frozen parts, ensuring smooth operation when you need it most. Built tough to start wet engines and keep them running strong, 6-56® is your go-to defense against the elements.

Applications

Fishing reels, winches, pulleys, metal components, starts wet engines, frees rusted parts, as a corrosion inhibitor

Identification

Item Number / Case Number	1003879 / 1003878
Legacy Number	06006
Unit Package Description	12 Ounce Aerosol
Net Fill	9 wt oz
UPC Code	078254060064
Unit Dimensions	6.25H x 2.63W x 2.63D in
Units Per Case	12

Properties

Appearance	Clear to Hazy Blue-Green Liquid
Base Type	Petroleum
Boiling Point (F/C)	380°F (Initial) / 193°C
Dielectric Strength	38,800 Volts
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
Evaporation Rate	Slow
Flash Point (F/C)	192°F / 89°C
Flammability LEL % / UEL %	0.6 / 5.5
Flammability Class - CPSC	Flammable
NSF Category Code	N/A
Odor	Pleasant
Plastic Safe	Not on all plastics
Propellant	Carbon Dioxide
Restricted From Sale In:	
Solubility	Water - Negligible
Spec Gravity Concentrate	0.827
Vapor Density	> 1 (air = 1)
VOC % (Consumer Product def)	0
VOC Category	Multi-Purpose Lubricant
Working Temp (F/C)	-50 to 250°F / -45.6 to 121.1°C

Sizes

5 wt oz	06005
9 wt oz	06006
11 wt oz	06007
1 gal	06008
5 gal	06010



For more information: 800-556-5074 • cxus@crcind.com • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty products and formulations for the do-it-yourselfer and maintenance professional, serving the automotive, industrial, electrical, marine, heavy truck, hardware, and aviation markets.