



TECHNICAL INFORMATION



V2 Slight Variation



Ready Ship



Recommend offset pattern $\leq 33\%$



DCOF: ≥ 0.42



Frost Resistant



Water Absorption: $\leq 0.5\%$



COLORS



Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
32" x 32" Rectified	31.44" x 31.44"	10 mm	Matte
12" x 24"	11.81" x 23.81"	8.5 mm	Matte
3" x 15" Brick Rectified	2.48" x 15.75"	12 mm	Matte
12" x 36" Fjord Deco Rectified	11.75" x 35.37"	12 mm	Matte
12" x 12" Mosaic Rectified	11.73" x 11.73"	8.5 mm	Matte
3" x 12" Bullnose Rectified	2.75" x 12"	8.5 mm	Matte

* Not all sizes are available in all colors and finish

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Performance Characteristics

Breaking Strength	N/A
Chemical Resistance	Resistant
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	N/A
Water Absorption	$\leq 0.5\%$
Certifications	N/A
Country of Origin	N/A
Shade Variation Code	V2



Please see virginiatile.com for details