Rigid/Intermediate Grade Conduit Fittings

Push Plugs, Snap-in Blanks, Reducing Washers

PUSH PLUGS – PLASTIC

Applications:

- Used to plug knockouts on enclosures to prevent moisture, dust and debris from entering the enclosure during shipment or install
- Plugs are wider than size listed to ensure secure connection in enclosure
- Temperature rating: 180°F to 200°F
- Tensile strength: 600-2300 PSI



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
PPC 50	½"	100	1
PPC 75	¾"	100	1
PPC 100	1"	50	1
PPC 125	1¼"	50	1
PPC 150	1½"	25	1
PPC 200	2"	25	1
PPC 250	2½"	100	2
PPC 300	3"	100	3
PPC 350	3½"	50	6
PPC 400	4"	50	8

KNOCKOUT SNAP-IN BLANKS – STEEL

Applications:

- Used to plug knockouts in steel boxes
- Snap-in blanks press firmly into knockout, providing a secure connection



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
335	½"	100	2
336	¾"	100	2
337	1"	50	2
338	1¼"	50	3
339	1½"	50	5
340	2"	20	7

KNOCKOUT REDUCING WASHERS – STEEL

Applications:

- Used with steel boxes to reduce the knockout size
- Reducing washers press firmly into knockout, providing a secure connection

UL File No. E-23223



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
342	¾" - ½"	100	1
343	1" - ½"	100	2
344	1" - ¾"	100	2
345	1¼" - ½"	100	3
346	1¼" - ¾"	100	2
347	1¼" - 1"	100	2
348	1½" - ½"	50	5
349	1½" - ¾"	50	4
350S	1½" - 1"	50	4
351	1½" - 1¼"	50	3
352	2" - ½"	50	7
353	2" - ¾	50	7
354	2" - 1"	50	6
355	2" - 1¼"	50	5
356	2" - 1½"	50	3
360	2½" - ½"	25	7
361	2½" - ¾"	25	7
362	2½" - 1"	25	7
363	2½" - 1¼"	25	7
364	2½" - 1½"	25	7
365	2½" - 2"	25	7
366	3" - 1"	25	14
367	3" - 1¼"	25	14
368	3" - 1½"	25	14
369	3" - 2"	25	14
370 S	3" - 2½"	25	14
371*	3½" - 1½"	25	25
372*	3½" - 2"	25	25
373*	3½" - 2½"	25	25
374*	3½" - 3"	25	25
375*	4" - 2"	25	35
376*	4" - 2½"	25	35
377*	4" - 3"	25	35
378*	4" - 3½"	25	35

*Not UL Listed.

 Copyright© 2015 Commercial Products Catalog

Concrete Slab Inserts

CONCRETE SLAB INSERTS – 90 DEGREE

Applications:

- For use with rigid and IMC
- For conduit installed in poured concrete slabs
- 90 degree design eliminates the need to bend conduit
- Provides flush threaded conduit hub for connecting rigid and IMC conduit and allows future access to conduit system
- Used in in-slab ceiling and floor poured applications

Standard Material:

- Zinc die cast





Cat. #	EMT	Unit Qty.	Wt. Lbs. Per 100
ESL75	3/4"	5	41
ESL100	1"	5	57

Dimensions (in Inches):

Cat. #	A	B	C	D	E	F	G
ESL75	4.55	3.72	3.49	3.15	2.13	1.14	0.20
ESL100	4.68	3.84	3.46	3.10	2.44	1.47	0.19

