

GUARANTEED TOUGH:



DPG22 TYPE II SAFETY HELMETS

The DEWALT DPG22 and DPG22V Type II Safety Helmets feature a durable polycarbonate shell with a comfortable EPS foam liner for the highest level of top and side impact protection on the market. Articulating smooth glide ratchet placement and the 4-point retention straps allow multi-point adjustability.





Adjustable 4-point leather chin strap secures helmet to head and provides comfortable fit.



Smooth glide, articulating ratchet adjustment dial for quick, secure fit.



| NON-VENTED | |
|--------------|------------|
| Item | Color |
| DPG22-WHITE | WHITE |
| DPG22-YELLOW | YELLOW |
| DPG22-SLATE | SLATE GRAY |

















△WARNING: Cancer and reproductive harm - www.P65warnings.ca.gov

WHY TYPE II HEAD PROTECTION?

DEWALT Type II Safety Helmets offer unparalleled protection in diverse scenarios involving climbing and possible head impact. The DEWALT Type II helmet offers a brimless design for a greater field of vision, a lower profile for enhanced mobility, and a 4pt chin strap to help keep the helmet securely in place when climbing, looking around or in the event of a fall.

Whether it's ascending ladders, navigating scaffolding, working on power or telecom poles, or engaging in tasks that demand fall protection. DEWALT Type II helmets provide indispensable protection. In contrast to Type I helmets, Type II helmets offer comprehensive protection against impacts from various angles and rotations, making them essential in industries with a heightened risk of lateral impacts.



RELATED ACCESSORIES

The DEWALT DPG22 and DPG22V Type II Safety Helmets feature accessory slots for shaped visors and cap mount earmuffs for added protection.

SHAPED VISOR **FOR TYPE II HELMET**

- Premium coating on AF+ lenses meets "X" anti-fog performance requirements
- Made for use with DPG22 helmets
- Meets ANSI Z87.1+
- · Can be worn with most eyewear













| Item | Lens |
|------------|----------------|
| DPG22-SH13 | CLEAR AF+ |
| DPG22-SH23 | SMOKE AF+ |
| DPG22-SH90 | INDOOR/OUTDOOR |





DIELECTRIC CAP MOUNT EARMUFF

- Designed for DEWALT Type II helmets (also fits most slotted hard hats)
- Reinforced pivot point
- · Padded earcups
- Low profile
- Lightweight



| Item | Description |
|----------|----------------|
| DPG660-D | NRR 25 Earmuff |



Helmet sold separately.









HEAD PROTECTION: ANSI/ISEA Z89.1-2014 (R19)





- American National Standard for Industrial Head Protection
- Provides (1) performance (2) testing and (3) labeling requirements for industrial hard hats.
- It establishes the types and classes of protective helmets, depending on the type of hazard encountered

SAFETY HELMET TYPES


ANSI TOP IMPACT (TYPE I)

Helmets designed to reduce the force of impact resulting from a blow to the top of the head.

ANSI TOP AND LATERAL IMPACT (TYPE II)

Provides impact to (90 degrees from vertical). Type 2 helmets require a larger foam interior and increased side coverage.





MAX FORCE

ANSI SAFETY HELMET ELECTRICAL CLASSES

To improve comprehension and usefulness, there are electrical-protective classifications for helmets as follows:

GENERAL



- Intended to reduce the danger of exposure to low voltage electrical conductors
- Proof tested at 2,200 volts @ 1 minute

ELECTRICAL



- Intended to reduce the danger of exposure to high voltage electrical conductors
- Proof tested at 20,000 volts @ 3 minutesAnd no burn through @ 30,000 volts
- Class E supersedes class G

CONDUCTIVE



Helmets NOT intended to provide protection from electrical conductors.

EYEWEAR PROTECTION: ANSI/ISEA Z87.1-2020 / "X" ANTI-FOG

The DEWALT shaped visor has been tested as an impact-rated (+) protector and meets the anti-fog performance (X) requirement per ANSI Z87.1-2020.

HEARING PROTECTION: ANSI/ISEA S3.19-197

DEWALT cap mount earmuff is tested to ANSI S3.19 with a NRR 25.

