



FEATURES

APT[™]X ADAPTIVE AUDIO

BUILT-IN HI-RES BLUETOOTH AUDIO TRANSMISSION TO YOUR COMPATIBLE SPEAKERS AND HEADPHONES

HIGH QUALITY MATERIALS

LOW-RESONANCE VENEERED MDF PLINTH WITH PREMIUM METAL TURNTABLE COMPONENTS AND PLATTER

PREMIUM TONEARM

CARBON FIBER TONEARM WITH CUSTOM-DESIGNED REMOVABLE HEADSHELL AND ADJUSTABLE COUNTERWEIGHT

ORTOFON 2M RED CARTRIDGE

BRINGS INCREDIBLE, DYNAMIC SOUND AND ITS SIGNATURE TOUCH OF WARMTH

USER-FRIENDLY FEATURES

SWITCHABLE PRE-AMP WITH RCA OUTPUT AND AUTO-STOP SENSOR TO PREVENT STYLUS WEAR

SPECIFICATIONS

POWER INPUT:	AC 100-240V ~ 50HZ/60HZ
SUPPORTED BLUETOOTH CODECS:	QUALCOMM [®] APTX [™] ADAPTIVE, APTX [™] HD, APTX [™] , SBC
OUTPUTS:	RCA (BUILT-IN PREAMP), PHONO
MATERIAL:	MDF, ALUMINUM, PLASTIC & CARBON FIBER
DIMENSIONS:	W 16.93" X L 14.25" X H 4.53"
WEIGHT:	6.15 KGS / 13.56 LBS (W/ COVER)
ACCESSORIES INCLUDED:	DUST COVER, 45 RPM ADAPTER, 6' RCA CABLE WITH GROUND

TURNTABLE SPECS

DRIVE METHOD:	BELT-DRIVE
PLATTER:	DIE-CAST ALUMINUM
CARTRIDGE:	ORTOFON 2M RED
MOTOR:	DC SERVO-CONTROLLED
SPEEDS:	33-1/3 RPM & 45 RPM
PHONO PRE-AMP GAIN:	35 DB NOMINAL, RIAA EQUALIZED
SIGNAL-TO-NOISE:	>45 DB
WOW & FLUTTER:	<0.175
TONEARM LENGTH:	225 MM
OVERHANG:	18.50 MM
TRACKING ERROR ANGLE:	<2 DEGREES

