

LED Decorative Cloud CCW



The Softer Side of **LED**

CCW

The **CCW LED Decorative Cloud** offers general ambient lighting for surface mount ceiling applications and is available in both standard and high output lumen packages to allow for design flexibility. The rounded edges of the acrylic lens offer a soft aesthetic while allowing for maximum light output. The CCW is the perfect energy-saving solution for both remodel and new construction in residential and light commercial applications such as kitchens, garages, utility rooms, schools, offices and hallways.

Mounting

Durable body allows for surface mounting to ceilings.

Dimmable High Performing LEDs

Driver delivers full-range dimming from 0 - 10VDC.

Rounded Edges

Smooth, rounded edges allow for safe handling.

Decorative Cloud Diffuser

Premium acrylic lens eliminates hotspots and provides a soft uniform distribution.


NICOR Lens-Lock™

Take advantage of NICOR's Lens-Lock™ system which allows for easy access during installation and tightly secures the lens in place, even on sloped ceilings.

Unlocked



Locked





Construction

- Heavy 20 gauge steel construction
- Smooth sides for safe handling
- NICOR Lens-lock™ secures lens in place, even on sloped ceilings

Optical System

- Full length acrylic diffuser for even light distribution

Electrical

- Utilizes high performing, mid-power LEDs
- Available in standard and high output options
- Driver delivers full-range dimming from 0 - 10VDC
- Silent and flicker-free operation
- Tight LED binning ensures color uniformity
- Operating temperature of 0° to 120°F (-18°C to 40°C)
- Universal input 120-277VAC
- TM-21 reported L70(9K) > 54,000
- LM-79, LM-80 testing performed in accordance with IESNA standards
- Meets FCC Part 15:2006 Class B requirements

Finish

- White powder coat finish

Installation

- Quick surface mount installation
- Driver and internal components easily accessible via removable lens

Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the fixture or electrical distribution panel

4S



4H



PRODUCT INFORMATION	CCW-10-4S-UNV-40K	CCW-10-4H-UNV-40K
TM-21 Projected L70(9k) LED Lifetime:	>90,000 Hours	>90,000 Hours
Input Voltage:	120-277V	120-277V
Power Draw:	39W	49W
Delivered Lumens:	3340	4675
System Efficacy:	84 Lm/W	94 Lm/W
Dimmable:	0-10V	0-10V
Correlated Color Temp:	4025K	4025K
Fixture Height:	4 in. (101mm)	4 in. (101mm)
Trim Width:	11.5 in. (292mm)	17 in. (432mm)
Length:	51.5 in. (1308mm)	51.5 in. (1308mm)



Ordering Information

Example: CCW-10-4H-UNV-30K

Series	Version	Lamp Equivalent	Voltage(V)	CCT's
CCW	10 (v1.0)	4S (standard output)	UNV (120-277V)	30K (3000)
		4H (high output)		40K (4000)
				50K (5000)

Warehouse Locations

Albuquerque NM
Atlanta GA
Detroit MI
Miami FL
San Antonio TX
Syracuse NY
Indianapolis IN

T 800.821.6283

F 800.892.8393

www.nicorlighting.com

2200 Midtown Place NE
Albuquerque NM 87107 USA



LIT-CCW 1116

©2016 NICOR® • ALL RIGHTS RESERVED

