



SCALE 1:1

SECTION A-A

STATIC TORQUE RECOMMENDATION: 10-18 in-lbs  
 REQUIREMENT MAY VARY DEPENDING UPON CONTAINER MATERIAL,  
 NECK FINISH, AND CAPPING EQUIPMENT

THREAD DETAIL INFORMATION:	8 THREADS PER INCH	0.125" [3.18] PITCH	450° FULL DEPTH THREADS
----------------------------	--------------------	---------------------	-------------------------

REFERENCE	DIMENSION	TOLERANCE	UNITS
Ø E	0.868 [22.05]	±0.010 [0.25]	in [mm]
Ø T	0.955 [24.26]	±0.010 [0.25]	in [mm]
H	0.640 [16.26]	±0.010 [0.25]	in [mm]
OAH	0.690 [17.53]	±0.010 [0.25]	in [mm]
Ø OD	1.060 [26.92]	±0.010 [0.25]	in [mm]
PART WEIGHT	2.00	± 0.20	g

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG31517

DESCRIPTION:

24-410 White PP Plastic Matte Top, Ribbed Sides, .020 Pulp Liner Plain

# Safe-Gard™ Type A Technical Data Sheet

## .020" Pulp SG-75M

Revision: SG75M-03142016

### MRP DESCRIPTION - (076)SG75M.020 PL

<b>Product</b>	.020" Pulp SG-75M																				
<b>Scope</b>	Two piece white-lined pulp backed heat induction foil innerseal that will provide a tamper evident seal to PE containers.																				
<b>Composition</b>	<table border="1"> <thead> <tr> <th>Material</th> <th>Standard</th> <th>Metric</th> </tr> </thead> <tbody> <tr> <td>Pulp</td> <td>0.020"</td> <td>0.508mm</td> </tr> <tr> <td>Wax</td> <td>-</td> <td>-</td> </tr> <tr> <td>Foil</td> <td>0.001"</td> <td>0.025mm</td> </tr> <tr> <td>PET Film</td> <td>0.0005"</td> <td>0.013mm</td> </tr> <tr> <td>Heat Seal</td> <td>0.0015"</td> <td>0.038mm</td> </tr> </tbody> </table>	Material	Standard	Metric	Pulp	0.020"	0.508mm	Wax	-	-	Foil	0.001"	0.025mm	PET Film	0.0005"	0.013mm	Heat Seal	0.0015"	0.038mm		
Material	Standard	Metric																			
Pulp	0.020"	0.508mm																			
Wax	-	-																			
Foil	0.001"	0.025mm																			
PET Film	0.0005"	0.013mm																			
Heat Seal	0.0015"	0.038mm																			
<b>FDA Status:</b> 21 CFR 177.1210	<b>Recommended Storage and Handling:</b> Refer to website																				
<b>Drug Master File (DMF):</b> 3782	<b>EU / EP Reg.:</b>																				
<b>GTR Oxygen:</b> Essentially Zero	<b>MVTR:</b> Essentially Zero																				
<b>Sealing to glass containers:</b> Selig can not guarantee the performance or seal integrity of this materials when applied to any glass (treated or untreated) container. We suggest you contact your glass supplier for recommendations on glass treatments that may or may not improve performance or seal integrity.																					
<b>Print Location (if any):</b> On foil layer																					

Selig materials are compliant with limitation of heavy metals in packaging per CONEG & EU 94/62/EC, article 11.

MSDS's are not required as Selig is not a chemical manufacturer or distributor and our products are 'articles' intended for food packaging per 29 CFR 1910.1200 (HazCom).

The information contained within this product data bulletin is to be used as a general guide in determining which structures are offered for sealing to specific container materials. All of the information which we provide is reliable to the best of our knowledge, but the accuracy thereof is not guaranteed. We suggest that consumers determine suitability for their own application.

DISTRIBUTED BY:



REF NO.:

DWG31517

**DISCLAIMER**  
THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DESCRIPTION:

24-410 White PP Plastic Matte Top, Ribbed Sides,  
.020 Pulp Liner Plain