

ILLUSIONIST™
COLORBODY™ PORCELAIN

MARAZZI®
DARE TO BE BOLD™

CONCRETE LOOK



ILLUSIONIST™

Unveil your artistic ambition with the ColorBody™ porcelain masterpiece, Illusionist. This concrete look tile is inspired by the whimsical movement of watercolor paintings; the surface hosts a unique glossy effect that creates high definition and variation. The dreamy color palette includes a creamy white, smokey grays and a saturated blue, all available in an array of large format sizes, plus two statement color blends in the 1 x 24 mosaic. Bring your picture-perfect design to life with Illusionist.



COVER PHOTO: MIRAGE (FLOOR)
ABOVE PHOTO: LUMEN (FLOOR) & MAGICAL
(FEATURE WALL)

CONCRETE LOOK

FINISHES: MATTE



CONCRETE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

FLOOR TILE



IL45 Lumen



IL46 Mirage



IL47 Stage



IL48 Smoke



IL49 Mysterious

3 x 3 MOSAIC | 12 x 12 SHEET




IL45 Lumen




IL46 Mirage



IL47 Stage



IL48 Smoke



IL49 Mysterious

1 x 24 MOSAIC | 12 x 24 SHEET



IL50 Magical
(40% IL46 Mirage, 40% IL47 Stage
& 20% IL48 Smoke)



IL51 Mystifying
(20% IL47 Stage, 40% IL48 Smoke
& 40% IL49 Mysterious)



VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE
 FLOOR
 WALL
 COUNTERTOP
 SHOWER FLOOR
 EXTERIOR FLOOR

MATERIAL
 PC

PRICING
 LOW HIGH

SPECIAL FEATURES
 STEPWISE
 TRUEEDGE
 MADE IN THE U.S.A.
 LARGE FORMAT
 MOSAIC/DECO
 ENCAUSTIC
 TERRAZZO
 PAVER
 CUSTOMIZE

CONCRETE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 Floor Tile	23-3/8" x 46-15/16" (59.44 cm x 119.30 cm)	5/16"	15.26	2
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	15.21	4
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 x 59.44 cm)	5/16"	17.02	9
	1 x 24 Mosaic (Mesh-mounted)	11-5/8" x 23-3/8" Sheet (29.56 cm x 59.44 cm Sheet)	5/16"	7.56	4
	3 x 3 Mosaic (Mesh-mounted)	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	5/16"	7.00	7

TRIM

Description	Number	Size	Shape
Floor Bullnose	P43F9	3 x 24	

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* 3 x 3 Mosaic tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.) Mosaic: 1/8"	Random Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Results
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Not use for ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazziusa.com/Large Tiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

FEATURES

PRE-CONSUMER RECYCLED MATERIALS
 MADE IN THE U.S.A.

REVEAL IMAGING®

CERTIFIED PORCELAIN™
90% or more water absorbed

ZEROTox®
Healthy Homes Healthy Planet

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.

© 2023 Marazzi (1/23)