
UXP-NRA-12S

N Male Right Angle Connector for 1/2” Superflexible Cable





Installation video

Installation instructions

Contact technical support:
1-888-201-6073
techsupport@jmawireless.com

General	Specification
Interface/gender	N male right angle
Cables supported[1]	Andrew FSJ4, FSJ4RK, FSJ4RN-50; RFS SCF12; NK Draka RFF1200; Eupen EC4HF; Leoni Flexline 1/2"S; LS/Superior Essex HFSC 12D; Hansen RF5012S, RF5012SZ; Rosenbeger SL 1/2" S; HUBER+SUHNER SF 1/2 HF
Weight	166.9 g | 0.368 lb
JMA Weather Protection System	WPS-NRA-4S

Tools required	JMA part number	Comment
Cable preparation	SP-12S	No coring required
Connector compression	HCG-FRAMESET-1/2, HCG-CC	Insert A
Torque wrench	TW1412	14 lbf·in | 1.58 N·m

Frequency band	VSWR	Return loss (dB)
555–1000 MHz (0-1 GHz)	1.02	40
1000–2700 MHz (1-2 GHz)	1.03	38
2700–3800 MHz (2-4 GHz)	1.05	30
3800–6000 MHz (4-6 GHz)	1.08	26

Electrical	Specification	Comment
Connector impedance	50 ohm	
Operating frequency band	DC–6 GHz	
3rd order IMD dynamic, (PIM)	-161 dBc, typical	IEC 60237-02
DC test voltage	2000 V	
Center contact resistance	≤ 1.5 milliohm	
Outer contact continuity	0.3 milliohm max.	
Average power	600 W @ 900 MHz	
Peak power, max.	10 kW	
Insertion loss, typical	0.05 dB	Per connector
Shielding effectiveness	< -120 dB	@ 0-1 GHz

Mechanical	Specification	Comment
Pull force combined	.78 kN | >175 lb	Cable limited
Cable retention torque	6.7 N·m | 5 lbf·ft	Cable limited
Interface durability	500 cycles	IEC 61169-4:9.5

Environmental	Specification	Test
Operating temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Accelerated UV	1000 hr	ASTM G154
Immersion test method	Mated & unmated, IP68	IEC 60529:2001 & ANSI/SCTE 60
Water jetting test method	Mated & unmated, IP66	IEC 60529:2001
Mechanical shock test method	Pass	IEC 60068-2-27
Thermal shock test method	Pass	IEC 60068-2-14
Vibration test method	100 m/s^2, 2 Hz to 200 Hz	IEC 61169-1:2003
Corrosion test method	1000 hr	IEC 60068-2-11

[1]For cable types not listed, please contact JMA Technical Support.

02/07/20

©2020 JMA Wireless. All rights reserved. This document contains proprietary information. All products, company names, brands, and logos are trademarks™ or registered® trademarks of their respective holders. All specifications are subject to change without notice.
+1 315.431.7100 customerservice@jmawireless.com