RED ALERT® Emergency Telephone - Model 394AL-001

By Austdac
Catalog # 394AL-001



GAI-TRONICS' RED ALERT® Emergency Telephones are designed to provide clear and reliable communications in almost any environment. The model 394AL-00x is considered to be Type 3R weatherproof compliant when installed on any flat surface.

Features

- Weather-resistant (Type 3R) Surface-Mount Design
- Rugged Cast-aluminum Enclosure with Powder-coated Epoxy, Safety Yellow
- Telephone Line Powered, (No Battery or External Power Required for Telephone Operation)
- Large "Palm" Activation HELP Pushbutton For Emergency Call
- CALL Pushbutton for Standard Keypad Dialing
- 12-Button, Braille Keypad
- Standard or SMART Operation
- Auto Answer (with Silent Monitoring)
- (2) Programmable Auxiliary Outputs for Peripheral Equipment Control
- Operating Range of -20° C to +60° C
- Call Received When Lit LED
- 3-Number Rollover
- UL/CSA 60950 Compliant
- FCC Part 68 Certified
- ADA Compliant
- Monitored by TMA (Telephone Management Application) Software

General

Catalog Number	394AL-001
Color	Yellow
Connectivity Options	Analog
Mount location	Surface-Mount
Output Level Speaker	87 dB @ 1 M
Signal Type	Analog
Specifications	UL/CSA, FCC, IC
Type	• Emergency Telephones • Keypad
Weather Rating	Type 3R

Dimensions

Dimensions	4.0 in x 8.0 in x 9.5 in
Dimensions - Shipping	13.0 x 12.0 x 8.0
Height	9.5 in
Length	4 in
Weight	8.5 lb
Width	8 in

Electrical Ratings

Input Voltage	Phone Line
Signal	Phone Line

Certifications And Compliance

Certified Listed	UL/CSA, FCC, IC

Product Assets

Brochures - Red Alert Telephone Brochure
Installation Manuals - RED ALERT® 300 Series Emergency Telephone Manual
Literature - Telephone Management Application (TMA)
Literature - RED ALERT Hands-free Telephones
Specifications - 394AL001
Video - Gai-Tronics Emergency Phones

©2025 Hubbell Incorporated. All rights reserved