

**PRODUCT DESCRIPTION:** The 5518/34.25-G4/AS-11, the anti-stat version of the popular 5518/34.25-G4 insert, is also a straight-sided, seamless, vacuum-formed insert for 55-gallon open-head steel drums. It is molded from FDA-approved low-density polyethylene. A contoured lip snaps over the top bead to prevent leakage between the insert and the drum wall, while also providing easy drum closure using a standard ring and bolt or lock assembly.

## Insert Specifications

### MATERIAL USED

Low-density polyethylene (Anti- Stat)

### INSERT DIMENSIONS

Diameter: 22.5" (+0.25"/-0")

Height: 34.25" (+/-0.125")

Average thickness: 18 mil (+/-10%)

### WEIGHT

31.7 oz. (+/-10%)

### SIDE-WALL DESIGN

Straight-sided

### TEMPERATURE PARAMETERS

High (momentary): 175° (195°)F

Low: -40° F

### ANTI-STAT

Standard: MIL-B-81705-C

Resistivity rating: 10<sup>11</sup> Ω/Sq. typical

## Packaging Specifications

### CARTON WEIGHT

34 lb.

### CARTON DIMENSIONS

Length: 35"

Width: 21"

Height: 15"

### QUANTITY/CASE

15

### PACKAGING STYLE

Folded

CDF's ANTI-STAT LINERS CONTAIN AN INTERNAL ANTI-STAT AGENT THAT IS INTENDED AS AN AID TO REDUCTION OF STATIC BUILD-UP. THEY ARE NOT DESIGNED AS, AND SHOULD NOT BE USED AS, THE PRIMARY CONTROLLER OF STATIC ELECTRICITY IN A PROCESS. CDF'S ANTI-STAT LINERS SHOULD NOT BE USED IN ELECTRO-STATIC COATING SYSTEMS OR OTHER HIGHLY VOLATILE AREAS. PLEASE CONSULT YOUR SAFETY ENGINEER, SAFETY CONSULTANT, OR CDF IF THERE IS ANY QUESTION AS TO APPROPRIATENESS OF USE.

**TYPICAL APPLICATIONS:** The 5518/34.25-G4/AS-11 is ideal for drums using follower plates, or users who prefer a straight-sided insert. It is perfect for heavy-duty mixing, pumping and storing all liquids, powders and pastes that can be contained in low-density polyethylene. The anti-stat additive helps to reduce static build-up in static sensitive applications compatible with low-density polyethylene such as paints, volatile materials and fine powders.

### DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG20610

DESCRIPTION:

55 gal 18 mil LDPE Anti-Stat