

# Eaton MLLA2-UNV1-S903-EM1-P-M2

Catalog Number: MLLA2-UNV1-S903-EM1-P-M2

Eaton Crouse-Hinds series Champ MLLA linear LED, Cool white, 3/4" entries, Painted gray epoxy, 2 ft, Polycarb lens, 4000 lm, 132 lm/W, Copper-free alum, Flush ceil mt, Wide, >0.92 PF, Integral emerg battery, 120-277 Vac, 127/250 Vdc, 30W

## General specifications



### Product Name

Eaton Crouse-Hinds series Champ  
MLLA linear LED light fixture

### Catalog Number

MLLA2-UNV1-S903-EM1-P-M2

### UPC

786689716752

### Product Length/Depth

25.94 in

### Product Height

4.42 in

### Product Width

7.13 in

### Product Weight

19.1 lb

Photo is representative



## Certifications and compliances

### Area classification

Hazardous/Classified Locations

### Standards type

NEC/CEC

### NEC hazardous rating

Class I, Division 2

Class I, Zone 2

Class II, Division 1

Class III

### NEMA Rating

4X

### Ingress protection (IP) ratings

IP67

IP66

## Product specifications

### Lamp type

LED

### Color temperature

Cool white

### Lamp length

2 ft

### Lumens

4000

### Lumens per watt

132

### Optical distribution

Wide

### Mounting Method

Flush ceiling

### Voltage rating

120-277 Vac, 127/250 Vdc

## Resources

### Brochures

[Crouse-Hinds series Champ MLLA LED Linear brochure](#)

[Crouse-Hinds series Global LED lighting portfolio](#)

### Catalogs

[Crouse-Hinds series Champ MLLA LED Linear catalog page](#)

### Certification reports

[Champ MLLA and Pauluhn DLLA Linear LED and Champ VMVL Intelligent LED Fixtures UL certification \(Marine\)](#)

[Champ MLLA Hazardous Area Linear LED Light Fixtures UL certification \(MLLA4 with Battery Back-up\)](#)

[Champ MLLA Hazardous Area Linear LED Light Fixtures Canadian certification](#)

[Champ MLLA Hazardous Area Linear LED Light Fixtures UL certification](#)

### Installation instructions

[IF 1946 - MLLA-M2 Linear LED with Emergency Battery Back-up](#)

[IF 1939 - Champ Linear MLLA M2 LED Light Engine Fixtures](#)

Frequency rating

50/60 Hz

Lens material

Polycarbonate

Entry size

3/4"

Finish

Painted gray epoxy

Material

Copper-free aluminum

Wattage

30W

Power factor

> 0.92

Special features

Integral emergency battery back-up

IF 1932 - Champ Linear MLLA M2 LED Fixtures

Specifications and datasheets

Eaton Specification Sheet - MLLA2-UNV1-S903-EM1-P-M2

Champ MLLA LED Linear



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)