

Tahitian




Colors



White
VTL THWH



Brown
VTL THBR




Medium Gray
VTL THMG



Black
VTL THBL

Sizes



32" x 32" x 20.64mm Rectified



24" x 48" x 9.5mm Rectified



20" x 40" x 20.64mm Rectified



12" x 24" x 9.5mm Rectified

TAHITI AN

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
32" x 32" Textured Rectified	31.30" x 31.30"	20.64mm	Matte/Natural
24" x 48" Rectified	23.40" x 46.93"	9.50mm	Matte/Natural
20" x 40" Textured Rectified	19.49" x 39.17"	20.64mm	Matte/Natural
12" x 24" Rectified	11.81" x 23.62"	9.50mm	Matte/Natural

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
3" x 24" Bullnose	2.84" x 23.62"	Matte/Natural
6" x 12" Cove Base	5.91" x 11.81"	Matte/Natural
1" x 6" Cove Base Out Corner	1.00" x 6.00"	Matte/Natural

Recommended Grout Joint: 1/8" - Rectified
3/16" - Non Rectified

Product Characteristics

MATTE/NATURAL	
Breaking Strength (ASTM C648 or ISO 10545-4)	> 275 lbs
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	8
Water Absorption (ASTM C373 or ISO 10545-3)	< 0.5%
Certifications	N/A
Country of Origin	Italy
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Material

Glazed Color-Body Porcelain



Made in Italy



Ready Ship



V2 Slight Variation



DCOF: ≥0.42



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
SURFACES
COMMERCIAL