



### Specifications


- Solid copper construction and tin plated
- UL Listed 90° C, 600V to 35kV
- Die index traceable
- UL and CSA Listed

### Lug Reference

- Hole diameter:  $38 = 3/8" = 0.375"$
- Window: inspect wire position
- Barrel length: long series
- Die index: match with traceable die



## Standard Lugs




Style	Single		Double			
<b>H</b> Hole	0.25"	0.375"	0.25"	0.25"	0.375"	0.25"
<b>S</b> Spacing			0.625"	0.75"	1"	1.5"

Gauge	Qty	Color	Die Index	Single		Double		
6	50	Blue	7	HGBL06S*	HGBL06D*	HGBL06DA	HGBL06DB*	HGBL06DK
4	50	Gray	8	HGBL04S*	HGBL04D*	HGBL04DA	HGBL04DB*	
2	25	Brown	10	HGBL02S	HGBL02SA	HGBL02D*	HGBL02DA	HGBL02DB*
1	25	Green	11	HGBL01S	HGBL01SA	HGBL01D*	HGBL01DA	HGBL01DB*
1/0	10	Pink	12	HGBL10S	HGBL10SA	HGBL10D*	HGBL10DA	HGBL10DB*
2/0	10	Black	13		HGBL20SA		HGBL20DA	HGBL20DB*
3/0	10	Orange	14		HGBL30SA		HGBL30DA	HGBL30DB*
4/0	10	Purple	15					HGBL40DB*
250kcmil	5	Yellow	16					HGBL250DB
300kcmil	5	White	17					HGBL300DB
350kcmil	5	Red	18					HGBL350DB
500kcmil	5	Brown	20					HGBL500DB
600kcmil	5	Green	22					HGBL600DB
750kcmil	5	Black	24					HGBL750DB

Note: \*Add 1 to the end of the Catalog Number for Quantity 1

## Angled Lugs



Style	Single		Double			
<b>H</b> Hole	0.25"	0.25"	0.25"	0.25"	0.375"	0.25"
<b>S</b> Spacing			0.625"	0.625"	1"	1.5"
<b>A</b> Angle	45°	90°	45°	90°	90°	90°

Gauge	Qty	Color	Die Index	Single		Double			
6	50	Blue	7	HGBL06SF	HGBL06SN	HGBL06D45	HGBL06D90	HGBL06DB90	HGBL06DKN
6	1	Blue	7	HGBL06SF1		HGBL06DF1	HGBL06DN1		
4	50	Gray	8	HGBL04SF		HGBL04D45	HGBL04D90	HGBL04DB90	
2	25	Brown	10	HGBL02SF		HGBL02D45	HGBL02D90	HGBL02DB90	
1/0	10	Pink	12			HGBL10D45	HGBL10D90	HGBL10DB90	