



**Water Closet & Flushometer Combo**

**WETS-2450.1301**

**Product description**

Standard, ST-2459 Water Closet and ROYAL 111 ESS Flushometer.

**Compliances & Certifications**



(ADA Compliant, BAA Compliant, BABAA Compliant, BREEAM Water Credit, cUPC Certified, EPD, Green Globes Water, HPD, IAPMO, LEED Water, Satisfies LEED Credits, WELL Building Standard)

**Code 24501301**

**Downloads**

- [HET Wall Hung Installation Instructions.pdf](#)
- [Royal ESS Concealed and Exposed Installation Instructions.pdf](#)
- [Royal ESS 110\\_111 Electrical Box Installation Instructions.pdf](#)
- [SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf](#)
- [Optima ESS Repair and Maintenance Guide.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

**Videos**

- [Sloan – Company Overview](#)

---

## Details

- Flush Volume: 1.28 gpf (4.8 lpf)

---

## Features

- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037
- Designed to maximize and complement Sloan flushometers
- Universal model works with Sloan flushometers from 1.1 to 1.6 gpf
- Durable, hygienic vitreous china construction with elongated rim
- Syphonjet flushing achieves 1000g Map Scores when used with Sloan flushometers
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly

---

## Components

- Flushometer: Code 3450049
- Water Closet: Code 2102459

---

## Warranty

[View Warranty Information](#)

---

## Notes

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

