WOLVERINE BRASS, INC.
STAINLESS STEEL BALLCOCK CONNECTORS WITH 2 BRASS NUTS

CONSTRUCTION:
- ☐ CORROSION RESISTANT 302HQ STAINLESS STEEL BRAIDING.
- ☐ REINFORCED 2 PLY PVC INNER LINING.
- ☐ SUPERIOR STRENGTH AND FLEXIBILITY.
- ☐ 360 ° CIRCULAR CRIMPING.
- ☐ LONGER BARB AND PLATED BRASS SLEEVE.

OPERATION:
- ☐ TWO BRASS NUTS.
- ☐ BURST TESTED TO EXCEED 2500 PSI.

CATALOG #	DESCRIPTION	A
57663US	3/8" OD x 7/8"	6"
57664US	3/8" OD x 7/8"	9"
57670US	3/8" OD x 7/8"	12"
57665US	3/8" OD x 7/8"	16"
57666US	3/8" OD x 7/8"	20"
57667US	1/2" OD x 7/8"	9"
57668US	1/2" OD x 7/8"	12"
57669US	1/2" OD x 7/8"	20"
57584US	1/2" FIP x 7/8"	12"
57585US	1/2" FIP x 7/8"	16"
57586US	1/2" FIP x 7/8"	20"

