



# STONE LOOK







# COLORBODY™ PORCELAIN

DARE TO BE BOLD

FINISHES: MATTE









Рc























STONE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

#### **FLOOR TILE**









CV40 Ivory

CV41 Natural

CV42 Greige

CV43 Carbon

## **DECORATIVE TILE**









CV44 Lucca Blue

CV45 Lucca Greige

CV46 Siena Blue

CV47 Siena Greige

# **VERSAILLES DESIGN IDEAS**









CV40 Ivory | Pattern 3

CV41 Natural | Pattern 1

CV42 Greige | Pattern 2

CV43 Carbon | Pattern 4

# KEY



PATTERN 1 - PIECES PATTERN 2 - PIECES PATTERN 3 - PIECES PATTERN 4 - PIECES 16.6% of 24 x 36 33.4% of 24 x 24 16.6% of 12 x 24

33.4% of 12 x 12

14.3% of 24 x 36 14.3% of 24 x 24 42.8% of 12 x 24 28.6% of 12 x 12

16.6% of 24 x 36 33.4% of 24 x 24 16.6% of 12 x 24 33.4% of 12 x 12

16.6% of 24 x 36 33.4% of 24 x 24 16.6% of 12 x 24 33.4% of 12 x 12























FINISHES: MATTE

























STONE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

#### **SIZES**

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
12 x 12 Floor Tile	11-3/4" x 11-3/4" (29.80 cm x 29.80 cm)	3/8"	5.81	6
12 x 12 Deco Tile	11-3/4" x 11-3/4" (29.80 cm x 29.80 cm)	3/8"	5.81	6
12 x 24 Floor Tile	11-3/4" x 23-9/16" (29.80 cm x 59.80 cm)	3/8"	11.63	6
24 x 24 Floor Tile	23-9/16" x 23-9/16" (59.80 cm x 59.80 cm)	3/8"	11.63	3
24 x 36 Floor Tile	23-9/16" x 35-3/8" (59.80 cm x 89.80 cm)	3/8"	11.63	2

#### **TRIM**

Description	Number	Size	Shape
Floor Bullnose	P43F9	3 x 24	

#### **APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest  $^{\!\scriptscriptstyle\mathsf{TM}}\!$  , visit marazzitile.com/DCOF.

#### **APPLICATION NOTES:**

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

#### **INSTALLATION**

Grout Joint Recommendation	Shade Variation		
Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	Random Variation		

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

#### **DURABILITY**

Floor Surface Wear Resistance				
	1	Residential Bathrooms	3	All Residential / Light Commercial
	2	All Residential Areas	(4)	All Residential / Commercial

#### **NOTES**

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

### **FEATURES**



PRE-CONSUMER RECYCLED MATERIALS



**REVEAL IMAGING®** 



