

Design that shapes living.

BOUNDLESS

VIRGINIA TILE COMPANY

PORCELAIN TILE



STONE MEETS CEMENT

COLORS



Ivory VTC BDIV



Gray VTC BDGR



Brown VTC BDBR

Ivory

9mm



24" x 48" x 9mm Honed Rectified




24" x 24" x 9mm Honed Rectified




12" x 24" x 9mm Honed Rectified

MOSAIC



2" x 2" x 9mm Mosaic Honed Rectified



4" Chevron Mosaic x 9mm Honed Rectified

TRIM

3" x 12" x 9mm Bullnose Honed Rectified

Gray

9mm



24" x 48" x 9mm Honed Rectified




24" x 24" x 9mm Honed Rectified




12" x 24" x 9mm Honed Rectified

MOSAIC



2" x 2" x 9mm Mosaic Honed Rectified



4" Chevron Mosaic x 9mm Honed Rectified

TRIM

3" x 12" x 9mm Bullnose Honed Rectified

Brown

9mm



24" x 48" x 9mm Honed Rectified




24" x 24" x 9mm Honed Rectified




12" x 24" x 9mm Honed Rectified

MOSAIC



2" x 2" x 9mm Mosaic Honed Rectified



4" Chevron Mosaic x 9mm Honed Rectified

TRIM

3" x 12" x 9mm Bullnose Honed Rectified

TECHNICAL INFORMATION



While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the number of colors on each piece may vary significantly.



Water Absorption: <0.5%





Modifying the traditional 50% offset used in a brick pattern to a maximum of 33% - which doesn't affect the look of the pattern - when installing tile 18" or larger, will manage lippage.



DCOF: ≥ 0.42



Ready Ship

CARE AND MAINTENANCE

PORCELAIN CARE & MAINTENANCE

INITIAL CLEANING

Proper cleaning after installation is essential for future maintenance. Remove excess grout using clean water and a sponge. If grout leaves behind a white haze, it can be wiped off using a clean cloth after grout has cured. Stubborn residue may require the use of a grout haze remover solution or neutral detergent. Thoroughly rinse the area with clean water and dry with a clean towel or wet vacuum.

ROUTINE MAINTENANCE

Immediately wipe up any spills and clean the area using a damp cloth or sponge. Remove loose soil using a broom or vacuum. To remove stubborn surface debris, use a scraper or putty knife. Wipe the area with a PH-neutral and soapless cleaner. Rinse with clear water and wipe dry to prevent residue. Do not use cleaning wax, oil-based cleaners, ammonia, sealants, or products containing acid or bleach for routine maintenance. Avoid using abrasive cleaning products such as steel wool.

ILLINOIS

DOWNTOWN CHICAGO 345 N. Wells Suite 200 Chicago, IL 60654

ELK GROVE VILLAGE 1601 Estes Ave. Elk Grove Village, IL 60007

IOWA

CLIVE 2001 NW 92nd Ct. Clive, IA 50325

KANSAS

KANSAS CITY 5100 Kansas Avenue Kansas City, KS 66106

WICHITA 2140 W. Harry Court Wichita, KS 67213

MICHIGAN

FARMINGTON HILLS 24404 Indoplex Circle Farmington Hills, MI 48335

GRAND RAPIDS 3440 Broadmoor S.E. Grand Rapids, MI 49512

TROY 900 W. Maple Rd. Suite 100 Troy, MI 48084

LIVONIA CORPORATE HEADQUARTERS 28320 Plymouth Road Livonia, Michigan 48150

MINNESOTA

PLYMOUTH 1820 Berkshire Ln. North Plymouth, MN 55441

MISSOURI

SPRINGFIELD 2727 N. Lecompte Rd. Springfield, MO 65803

ST. LOUIS 9215 Dielman Industrial Dr. St. Louis, MO 63132

NEBRASKA

OMAHA 10501 | Street Omaha, NE 68127

OHIO

BROOKLYN HEIGHTS 4749 Spring Rd. Brooklyn Heights, OH 44131

WARRENSVILLE HEIGHTS 4670 Richmond Rd. Warrensville Heights, OH 44128

OKLAHOMA

OKLAHOMA CITY 5600 SW 36th St. Suite C Oklahoma City, OK 73179

TULSA 11915 East 51st St. Tulsa, OK 74146

WISCONSIN

MENOMONEE FALLS W135 N5511 Campbell Dr. Menomonee Falls, WI 53051



Good design is born of creativity and imagination, but as we build and renovate, update and expand, the materials we select will define the quality of the spaces we live in beyond what meets the eye.

