

STYLED IN ITALY. PROUDLY AMERICAN.

GET



atlas concorde  
USA





# GET

Contemporary surfaces with lived-in effect, to decorate indoor residential and commercial spaces with a young and metropolitan look.





GET

Get Greige 11<sup>3/4"</sup>x23<sup>5/8"</sup> - 30x60 cm



---

COLORS

COLORED BODY PORCELAIN STONEWARE



Almond



Greige



Moka

GET

Get Greige 11<sup>3/4"</sup>x23<sup>5/8"</sup> - 30x60 cm





# GET

COLORED BODY PORCELAIN STONEWARE

## GET

Get Moka 11<sup>3/4</sup>"x23<sup>5/8</sup>" - 30x60 cm





Compliant with standards ANSI A137.1-2012



## GET

Get Almond  $11\frac{3}{4}'' \times 23\frac{5}{8}''$  - 30x60 cm



# GET

SIZE - THICKNESS | 11<sup>3/4"</sup>x23<sup>5/8"</sup> - 30x60 cm  9 mm FINISH | MATTE



GET Almond  
11<sup>3/4"</sup>x23<sup>5/8"</sup> - 30x60 cm



GET Greige  
11<sup>3/4"</sup>x23<sup>5/8"</sup> - 30x60 cm



GET Moka  
11<sup>3/4"</sup>x23<sup>5/8"</sup> - 30x60 cm

## COORDINATING TRIMS




GET Almond



GET Greige



GET Moka



Bullnose  
3"x 24" - 7.2x60 cm





SLIGHT VARIATION

**V2**

Compliant with standards ANSI A137.1-2012



**GET**

Get Greige 11<sup>3/4</sup>"x23<sup>5/8</sup>" - 30x60 cm



Every Atlas Concorde USA porcelain stoneware collection is PTCA Certified. Under the program, established jointly by the Porcelain Tile Certification Agency (PTCA) and the Ceramic Tile Distributors Association (CTDA), manufacturers can “prove” their product is really porcelain (meeting the water absorption criteria of the American national standard - ASTM C373).



LEED (Leadership in Energy and Environmental Design) is a rating system created to encourage the construction of “green” buildings. Developed by the US Green Building Council and internationally recognized, it points out the necessary requirements to build eco-compatible projects, capable of functioning in sustainable and autonomous way in terms of energy consumption as well as having a low environmental impact throughout their entire life-cycle. Atlas Concorde USA is a member of the US Green Building Council.



Atlas Concorde USA products are low-emitting materials with zero emission of volatile organic compounds (VOC). This can contribute to the awarding of 1 LEED credit.



Atlas Concorde USA is a member of TCNA, a trade association representing manufacturers of ceramic tile, tile installation materials, tile equipment, raw materials, and other tile-related products. The Tile Council is recognized for its leadership role in facilitating the development of North American and international industry quality standards to benefit tile consumers.



The Ceramic Tile Distributors Association (CTDA) is an international association of distributors, manufacturers and allied professionals of ceramic tile and related products. CTDA connects, educates and strengthens tile and stone distributors. Atlas Concorde USA is a member of CTDA.







## COLORED BODY PORCELAIN STONEWARE



Compliant with standards ANSI A137.1-2012

SIZE - THICKNESS

11 3/4" x 23 5/8" - 30x60 cm ± 9 mm

FINISH

MATTE



V2

### SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

FIELD TILES - Available in all colors










Nominal size (in)	Thickness (mm)	Finish
11 3/4" x 23 5/8"	9 mm	Matte

MOSAICS AND COORDINATING TRIMS - Available in all colors

	Nominal size (in)	Thickness (mm)	Finish
Bullnose 3"x24"	2 7/8" x 23 5/8"	9 mm	Matte

Please refer to caliber chart for work sizes.  
Close joints are not recommended.

## PERFORMANCE & FEATURES

				Porcelain Tile Specification					
				Calibrated		Rectified			GET
						Minimum	Maximum		
REGULARITY CHARACTERISTICS		Nominal Size	ASTM C499	-3.00%	3.00%	-3.00%	2.00%	Compliant	
		Caliber Range (Variation from average facial dimension of sample)		-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant	
		Thickness <sup>(1)</sup>		N/A	Range: 0.40 in (1.02 mm)	N/A	Range: 0.40 in (1.02 mm)	Compliant	
		Wedging	ASTM C502	-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant	
		Warpage Edge	ASTM C485	-0.75% or -0.09 in (-2.3 mm) (*)	0.75% or 0.09 in (2.3 mm) (*)	-0.40% or -0.05 in (-1.3 mm) <sup>(2)</sup> or -1.8 mm <sup>(3)</sup> (*)	0.40% or 0.05 in (1.3 mm) <sup>(2)</sup> or 1.8 mm <sup>(3)</sup> (*)	Compliant	
		Warpage Diagonal		-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.40% or -0.07 in (-1.8 mm) (*)	0.40% or 0.07 in (1.8 mm) (*)	Compliant	
				All Porcelain Tiles					
STRUCTURAL CHARACTERISTICS		Water Absorption	ASTM C373	≤ 0.5%				≤ 0.5%	
BULK MECHANICAL CHARACTERISTICS		Breaking strength	ASTM C648	Average ≥ 250 lbf. (1.11 kN) Individual ≥ 225 lbf. (1.00 kN)				≥ 350 lbf. avg	
PHYSICAL PROPERTIES		Bond Strength	ASTM C482	≥ 50 psi (0.34 Mpa)				≥ 100 psi	
THERMAL AND IGROMETRIC CHARACTERISTICS		Resistance to Freeze/ Thaw Cycling	ASTM C1026	As Reported				Resistant	
CHEMICAL CHARACTERISTICS		Chemical Resistance	ASTM C650	As Reported				Unaffected	
		Stain Resistance	ASTM C1378	As Reported				Unaffected	
SAFETY CHARACTERISTICS		Dynamic coefficient of friction	DCOF	Requires a minimum value of 0.42 for commercial areas that are likely to be wet				> 0.42 Wet	

(\*) Whichever is less

(1) May not apply to textured surfaces or tiles with uneven back patterns.

(2) Whichever is less, for tiles up to 24"x24" (610 mm x 610 mm).

(3) Applies to tiles larger than 24"x24" (610 mm x 610 mm).

Atlas Concorde reserves the right to modify any product without notice and will not be liable for any direct or indirect damage resulting from such modifications. Colors and optical features of the materials illustrated in this catalogue are to be regarded as mere indications. For information and details relating to codes, packaging and weight it is recommended to refer to the latest pricelist.

Atlas Concorde Usa, Inc.  
117 Seaboard Lane - Suite 170  
Franklin, TN 37067 - USA