



## VISTA-15P

### VISTA® Control Panel

The Honeywell HomeVista family of products is among the most widely recognized and reliable brands in the industry with the largest security system install base in the world.

The versatile VISTA-15P offers options to send alarm signals, upload/download capability, and remote services via IP, 4G or LTE communications, improving the speed at which information can be delivered to and from the control panel. This maximizes system longevity and reduces service calls and future upgrade costs. The VISTA-15P has the broadest array of residential hardwired or wireless sensor zone options that protect life and property, creates awareness and convenience with environmental options like thermostat, water shut-off and lighting control, as well as advanced functions like audio control via Denon. VISTA also offers fixed-English, custom Alpha or touchscreen keypad displays, two-wire smokes detectors, connected home support through Tuxedo Touch® with the ability to customize system actions, and events using scene control.



## FEATURES AND BENEFITS

- IP and cellular radio alarm reporting and upload/download capability via iGSMV4G, GSMV4G, GSMX4G, LTE-XV and LTE-XA
- Z-Wave® thermostats, lights, locks, water shut-off, garage door, shades and audio control via Tuxedo Touch and VAM
- Six on-board hardwired zones
  - 16 hardwired expansion zones totalling 22
  - 26 wireless expansion zones
- Supports two graphic touchscreen keypads
- Eight independent keyfob zones allow wireless keys to be programmed without using any of the 26 zones
- Eight output devices
  - Relays (Model 4204 Relay Modules, or 4229 Expansion Module)
- Two low current on-board trigger outputs
- 50 Event Log viewable at system keypads with time/date stamp
- 32 system user codes
- Two installer configurable zone types allows the installer to “create custom zone types” by assigning all zone attributes
- Multiple actions on output devices depending on system “state”
  - Turns light off when system arms
  - Turns same lights on when system disarms
  - Flashes same lights when system is in alarm
- Built-in phone line cut monitor with programmable delay and annunciation options
  - Display on system keypads
  - Trigger local sounders
  - Trigger system bell
- Supports four-wire and up to 16 two-wire smokes
  - Works with Sentrol CleanMe™ maintenance signal

### SECURITY DEALER FEATURES

- Automatic System Load Shed
  - During extended AC power fail, the system battery will be disconnected to prevent irreversible battery failure. Reduces service calls to replace batteries.
- Dynamic Signaling
  - Reduces redundant reporting to the central station when multiple reporting methods are used; i.e. digital dialer and AlarmNet® radio

### VALUABLE END-USER FEATURES

- Now viewable on system keypads:
    - Exit countdown
    - Time and date display\*
    - Event log\*
  - Auto keypad backlighting on entry
  - Keyswitch arming
  - Programmable macro buttons and single-button arming
  - A variety of wireless remote controls for single-button operation
  - User Scheduling
    - Latchkey reports to pagers
    - Auto arm/disarm
    - “User access” time windows
  - Supports up to two numeric pagers
  - VIP Module allows system control from any touchtone phone
  - Chime by zone
  - Fully compatible with Honeywell HomeTotal Connect® Remote Services
- \*Requires custom alpha keypad

# VISTA-15P Technical Specifications

## ELECTRICAL

Aux. power 12VDC, 600mA maximum  
Seven hour standby at 400mA aux. load  
with four amp hour battery  
16.5 VAC/25 VA transformer  
Alarm output 12VDC, 2.0 amps max.  
For UL installations, combined aux. and  
alarm output cannot exceed 700mA

## OUTPUT CONTROL

Supports a maximum of eight output  
devices (combination of relays and/or  
X-10) plus two onboard triggers

## ZONES

Six hardwired zones  
Selectable response 10msec, 350msec,  
750msec  
16 selectable zone types plus two  
configurable zone types  
Programmable swinger suppression

## EXPANSION DEVICES

4219 – Eight hardwired zones – 16mA  
4204 – Up to four relays – 15mA standby  
(each active relay draws an  
additional 40mA)  
4229 – Eight hardwired zones and two  
relays – 36mA (each active relay  
draws an additional 40mA)

## ACCESSORIES

iGSMV4G Internet and Digital Cellular  
Communicator with Remote Service  
Capability  
7845i-ENT Enterprise Internet  
Communicator  
GSMV4G Digital Cellular Communicator  
with Remote Service Capability  
GSMX4G Digital Cellular Communicator  
for VISTA Control Panels

5881ENL supports up to 8 zones – 60mA  
5881ENM supports up to 16 zones – 60mA  
5881ENH supports up to 48 zones – 60mA  
5883 Transceiver supports up to 26  
zones – 80mA

## KEYPADS

6160 Custom Alpha Security Keypad  
– 40mA/120mA  
6160V Voice Custom Alpha Security  
Keypad – 60mA/190mA  
6160RF Custom Alpha Receiver/Security  
Keypad – 120mA/210mA  
6150 Fixed-English Security Keypad  
– 40mA/70mA  
6150V Voice Fixed-English Security  
Keypad – 60mA/190mA  
6150RF/6150RFFR Fixed-English/  
French Receiver/Security Keypad  
– 80mA/105mA  
6151ZN/6151ZNFR Fixed-English/  
French Security Keypad with Hardwired  
Zone – 35mA/80mA  
6148 Fixed English LCD – 30mA/55mA  
6280 Color Graphic Touchscreen Keypad  
with Voice  
Tuxedo Touch (TUXWIFIW) Color Graphic  
Voice Touchscreen Security Keypad  
with 232 Z-Wave device and 32-camera  
support

## AGENCY LISTINGS

### UL listing

Residential Fire and Burglary:  
– Household Fire Warning System  
Units – ANSI/UL 985, 2000/05/26  
(5th edition) with revisions up to  
2004/04/29

## SMOKE DETECTORS

Supports up to 16 two-wire smoke  
detectors  
Supports four-wire smoke detectors  
Supports the 5800COMBO Smoke and  
Carbon Monoxide Detector

## COMMUNICATIONS

LTE-XV and LTE-XA Digital Cellular  
Communicators with Remote Service  
Capability  
iGSMV4G Internet and Digital Cellular  
Communicator with Remote Service  
Capability  
7847i-E Enterprise Internet  
Communicator  
7847i AlarmNet Internet Communicator  
GSMV4G Digital Cellular Communicator  
with Remote Service Capability  
GSMX4G Digital Cellular Communicator  
for VISTA Control Panels  
Touchtone or pulse  
Formats supported  
– ADEMCO® Contact ID  
– ADEMCO 4 + 2 Express  
– ADEMCO low speed  
– SESCOA/Radionics  
3 + 1, 4 + 1 and 4 + 2 reporting  
Reporting capabilities  
– Split  
– Dual  
– Split/Dual – True dial tone detection  
Low battery reports 11.2 – 11.6 VDC  
AC loss and restoral reporting supported

## ORDERING

VISTA-15P	Control Panel
VISTA-15PSIA	Control Panel for CP



### Resideo Technologies, Inc.

2 Corporate Center Drive, Suite 100  
P.O. Box 9040  
Melville, NY 11747  
1-800-645-7492  
resideo.com

### For more information

[security.honeywellhome.com](http://security.honeywellhome.com)

L/VISTA15PD/D | 09/19  
© 2019 Resideo Technologies, Inc.  
This product is manufactured  
by Resideo and its affiliates. The  
Honeywell Home trademark is  
used under license from Honeywell  
International Inc. All rights reserved.

**Honeywell Home**