17014A-LED-ID

6" IC Airtight Shallow LED Housing

Product Description

The 17014-LED-ID is a new construction, IC rated, Airtight thermally protected 6" shallow housing. Perfectly suited for NICOR D-Series LED downlights The 17014-LED-ID is suitable for condominiums, apartment buildings, multi-family, commercial and residential applications.

Housing

- Aluminum construction provides greater heat dissipation.
- Washington State Energy Code approved to meet restricted airflow requirements.
- Airtight housing limits the exchange of air between ceiling plenum and conditioned spaces.
- Integral thermal protector guards against improper lamping and misuse of insulation materials.
- 5 3/4" height allows use in 2"x 6" joist construction.

Plaster Frame

- Housing is secured to plater frame with screws and can be removed for access to junction box.
- Housing adjusts from 1/2" to 1 1/2" to accommodate ceiling thickness.

Junction Box

- Listed for through branch circuit wiring and includes several 3/4" knockouts.
- · Four pry-outs with integral strain relief simplify Romex installation

Hanger Bars

- Heavy-gauge NICOR captive hanger bars provide greater stability, allowing housing to be positioned at any point within a 24" joist span, then locked in place with set screws.
- Score lines allow bars to be shortened without any tools to accommodate a 12" joist span.
- Rotating hanger bar feet allows for easier one person installation.
- Unique hangar bar lip design help align can to joist.
- Four double-headed captive nails provided for ease of installation.
- Bars can be repositioned 90° on plaster frame without tools.
- Bars fir onto T-bar spine for quick alignment in commercial setting and can be permanently secured.

Listings

- Input voltage of 120VAC
- Approved under UL1598
- UL Listed for Damp Location
- UL Listed for Insulation Contact (Batt and Blown Fiberglass)
- Meets or exceeds ASTM-283 Air-Tight Requirements

Warranty

- 1-year warranty
- See www.nicorlighting.com for full details


Project


Catalog

Туре

Date









Ordering Information

Series

17014A-LED-ID

Specifications and dimensions subject to change without notice.

