

## TandemLED Wired Controller



In-line Switch for on / off / dimming / multi-white color tuning





Click between preset color temperatures of Warm White (2700K), Soft White (3000K), Cool White (4000K), Daylight White (5000K), or press and hold to achieve desired white color temperature.

## **TANDEMLED WIRED CONTROLLER**

PART NUMBER	DESCRIPTION / OUTPUT	DIMENSIONS
T-TIL-96	96 watt TandemLED™ Multi-White Color Tunable Wired Controller. Allows you to press one button to click through 2700K, 3000K, 4000K, and 5000K white color temperatures. The other button allows you to turn the multi-white lights on / off / or dim to a certain brightness. Included Wave Sensor (optional) allows you to wave hand in front of sensor to turn lights on / off.	3-9/16" x 1-9/16" x 7/8"

## **FEATURES**

- Wired Controller to tune multi-white light from Warm White to Daylight White and all white temperatures in between
- · Wave Sensor included (optional) for easy on / off
- · 3-year limited warranty
- · Designed for indoor application

## **COMPATIBLE POWER SUPPLIES**

PART NUMBER	DESCRIPTION	DIMENSIONS
T-12W-12V-PI	12 watt AC/DC 2 prong plug-in, 12 volt DC 1 AMP.	2-15/16" x 1-3/16" x 1-13/16"
T-24W-12V-PI	24 watt AC/DC 2 prong plug-in, 12 volt DC 2 AMP.	3-11/16" x 1-7/8" x 1-5/16"
T-36W-12V-PI	36 watt AC/DC 2 prong plug-in, 12 volt DC 3 AMP	3-3/4" x 2" x 1-5/16"
T-60W-12V-PI	60 watt AC/DC 2 prong plug-in, 12 volt DC 5 AMP	5-1/8" x 2-1/16" x 1-1/4"
T-96W-12V-PI	96 watt AC/DC 3 prong plug-in, 12 volt DC 8 AMP.	5-1/2" x 2-3/8" x 1-3/8"
T-120W-12V-PI	120 watt AC/DC 3 prong plug-in, 12 volt DC 10 AMP	6-3/8" x 2-11/16" x 1-1/4"
T-60W-12-WP-HW	60 watt, 12 volt IP67 rated waterproof LED hardwired	6-1/2" x 1-5/8" x 1-1/4"
T-150W-12-WP-HW	150 watt, 12 volt IP67 rated waterproof LED hardwired.	7-3/8" x 2-3/8" x 1-1/2"