SONANCE

VISUAL EXPERIENCE DATA SHEET

VX66

TECHNICAL SPECIFICATIONS

VX66

SKU 96004 - Pair

Tweeter 1" (25mm) ceramic dome, Ferrofluid-cooled,

acoustic back chamber

Woofer 6.5" (165mm) Kevlar/Nomex cone,

rubber surround

Dispersion Technology Sinusoidal textured waveguide

Frequency Response 43Hz - 20kHz +/-3dB

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling (RMS) 5 watts minimum; 140 watts maximum

Sensitivity (2.83V/1m) 90dB SPL

Mounting Technology Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps

 Micro Trim Grille (WxH)
 8.23" x 12.12" (208.9mm x 307.7mm)

 Trimless Grille (WxH)
 7.88" x 11.77" (200.1mm x 298.9mm)


Speaker Mounting Depth (D) 3.48" (88.3mm)

Mounting Depth + Retrofit Encl. 3.84" (97.6mm)

Cut-Out Dims (WxH) 6.9375" x 10.75" (176mm x 273mm)

Shipping Weight 10 lbs. (4.5kg)

DIMENSIONAL DRAWINGS




Cut-Out Width **Front View**



Mounting Depth (Open Back)

Side View



Mounting Depth + Retrofit Enclosure

Side View

VX 6" RECTANGLE ACCESSORIES

VX6-GRILLE-T

6" Micro Trim Rectangle Grille / Pair 93581

VX6-GRILLE-NT

6" Trimless Rectangle Grille / Pair 93582

VX6-ENCL

6" Rectangle Enclosure / Pair 96342

FLEXBRK-6

6" Rectangle Flex Bracket / 5x Pair 92336

LIMITED LIFETIME WARRANTY