SONANCE VISUAL EXPERIENCE DATA SHEET

VX64R

TECHNICAL SPECIFICATIONS

VX64R 96013 - Pair
1" (25mm) ceramic dome, Ferrofluid-cooled, acoustic back chamber
6.5" (165mm) textured polypropylene cone, rubber surround, pivoting
Sinusoidal textured waveguide
Coincident woofer and tweeter, +/-13° pivot
45Hz - 20kHz +/-3dB
8 ohms nominal; 6 ohms minimum
5 watts minimum; 125 watts maximum
89dB SPL
Flex Frame 1 or 2-stage, 4 x RotoLock $\ensuremath{\mathbb{R}}$ Clamps
9.62" (244.4mm)
9.28" (235.6mm)
9.62" x 9.62" (244.4mm x 244.4mm)
9.28" x 9.28" (235.6mm x 235.6mm)
4.92" (125mm)
5.75" (146.1mm)
8.25" (210mm)
9 lbs. (4.1kg)

.....


DIMENSIONAL DRAWINGS



Cut-Out Diameter Front View



Mounting Depth (Open Back) Side View



Mounting Depth + Retrofit Enclosure **Side View**

VX 6" ROUND ACCESSORIES

VX6R-GRILLE-T 6" Micro Trim Round Grille / Pair VX6R-GRILLE-NT	93575
6" Trimless Round Grille / Pair	93576
VX6SQ-T	
6" Micro Trim Square Adapter / Pair	96030
VX6SQ-T-5PR	
6" Micro Trim Square Adapter / 5xPair	96033
VX6SQ-NT	
6" Trimless Square Adapter / Pair	93586
VX6SQ-NT-5PR	
6" Trimless Square Adapter / 5xPair	93589
VX6-ENCL-R	
6" Round Enclosure / Pair	96343
FLEXBRK-6-R	
6" Round Flex Bracket / 5x Pair	92337
	02007

LIMITED LIFETIME WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the life of the Product, except for the grille, which is warranted for five (5) years. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. ©2024 Sonance. All rights reserved. Sonance product specification information visit our website at www.sonance.com. 991 Calle Amanecer • San Clemente, CA 92673 USA • Phone: (949) 492-7777 • Fax: (949) 361-5151 • Technical Support: (949) 492-7777 01.16.2024