



OAL VERSION COMPARISON



FIXTURE TYPE	OAL3	OAL4
FINISH COLOR	Bronze White	Bronze White
DIMENSIONS (150W ONLY)		
LENGTH	17.20"	20.00"
WIDTH	11.20"	10.50"
HEIGHT	2.50"	2.25"
ELECTRICAL INPUT		
INPUT VOLTAGE (VAC)	U 120-277V HV 277-480V	U 120-277V HV 277-480V
INPUT POWER (W)	150W (100/120/150W) 300W (200/240/320W)	150W (100/120/150W) 300W (200/240/320W)
TOTAL LUMEN OUTPUT (LM) FOR TYPE III ONLY	150W (12633 - 20769) 300W (25792 - 42459)	150W (14236 - 22826) 300W (28392 - 45653)
LUMINAIRE EFFICIENCY (LM/W) FOR TYPE III ONLY	150W (126.3 - 128.7) 300W (124.3 - 136.5)	150W (144.0 - 160.6) 300W (144.1 - 159.5)
COLOR TEMPERATURE (K)	CCT Select (30/40/50K)	CCT Select (30/40/50K)
CRI	80+	80+
DIMMING RANGE (%)	0-10V	0-10V
FEATURES		
WARRANTY	5 Year	5 Year
UL/ETL LISTED	Yes	Yes
IP65 RATED	Yes	Yes
OPERATING TEMPERATURE (°C)	-40 °C to 45 °C	-40 °C to 50 °C
LENS OPTIONS	Type II, III, IV, V (Field Swappable)	Type III-IV-V or Type II-III-IV (Selectable, Factory Installed)
12V ACCESSORY PORT	Yes	Yes
MULTI-MOUNT ARM	Not Available	Included with Fixture
MOUNTING BRACKETS	Adjustable Pole Mounting Slipfitter Mounting Straight Mounting Trunnion Mounting Wall Mounting	Adjustable Pole Mounting Slipfitter Mounting Straight Mounting Trunnion Mounting Wall Mounting