

# NICOR<sup>®</sup> OFL4

## FEATURES & BENEFITS



### 1. Visual Aesthetic & Application

The OFL4 LED Flood Light features a die-cast aluminum housing with a fine-textured, UV-stabilized powder coat finish for durability and heat dissipation. Stainless steel hardware ensures longevity in outdoor environments.



### 2. Performance

An impact-resistant polycarbonate lens delivers uniform light distribution with selectable NEMA beam patterns (5H5V, 6H6V, 7H6V). High-performance LEDs provide >80 CRI for enhanced visibility and color accuracy.



### 3. Control

Selectable CCT and wattage options allow on-site customization via switches located on the fixture's backside. Standard features include 0-10V dimming and a field-disableable photocell. The driver includes 6kV surge protection for reliability in varying power conditions.



### 4. Installation

Versatile mounting options include a pre-installed knuckle on 35W, 60W, and 80W models, and a slipfitter on 150W and 320W models. A trunnion is included with all fixtures, providing an adjustable range from 0° to 180°. A U-bracket mount is also available for additional flexibility. Surge protection is recommended in areas prone to power fluctuations.



### 5. Certifications

UL Listed for wet locations, IP65-rated for water and dust resistance, and RoHS compliant. Meets FCC Part 15, Subpart B, Class A standards. TM-21 Reported L70 life exceeds 43,800 hours, with LM-79 and LM-80 testing performed per IESNA standards.



### 5. Warranty

Backed by a 5-year limited system warranty. Additional surge protection is recommended for installations at risk of power surges.