


versatile™ 4C Mailbox, 4C15S-06



COMPARTMENT CHART

| DESCRIPTION | COMPARTMENT | COMPARTMENT SIZE | QTY. |
|---------------|-------------|--------------------------|------|
| MAILBOX | MB2 | 6-1/2" H x 12" W x 15" D | 5 |
| MAILBOX | MB3 | 10" H x 12" W x 15" D | 1 |
| OUTGOING MAIL | OM2 | 6-1/2" H x 12" W x 15" D | 1 |

Notes:

- This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - At least one customer compartment shall be positioned less than 48" above finished floor (AFF).
 - No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - No patron (tenant) lock shall be positioned more than 67" AFF.
 - No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - The USPS Arrow lock shall be positioned 36"- 48" AFF.
- This 4C mailbox can also be used for private applications.
- The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILE™ 4C FRONT LOAD MAILBOX

FLORENCE
CORPORATION

5935 Corporate Drive • Manhattan, KS 66503
800.275.1747 • www.florencemailboxes.com

| | | | |
|----------------|------------|---------------|----------|
| MODEL | 4C15S-06 | REV | E |
| SCALE | NONE | LAST REV DATE | 07/08/19 |
| DRAWING NUMBER | 4C15S-06CS | DRAWN BY | RAK |