


ASSEMBLY AND INSTALLATION INSTRUCTIONS

C0359

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: 1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. Read and save these instructions.

Hardware Package (included):




Installation Steps

Turn off the power at fuse or circuit box.

1. Unscrew the finial (D), remove the mounting strap unit (A) from the ceiling pan.
2. Attach mounting strap unit (A) to outlet box by using two mounting screws (B).
Note: The depth of threaded pipe on the mounting strap unit may need to be adjusted to properly fit the fixture.
3. Pull out the source wires from the outlet box, make wire connections using wire connectors (C) as follows:
 - Connect the black (hot) wire from the fixture to the black (hot) wire from the power source.
 - Connect the white (neutral) wire from the fixture to the white (neutral) wire from the power source.
 - Attach the fixture ground wire (bare wire) to the mounting strap unit (A) with the green ground screw, then connect fixture ground wire to the house ground wire with a wire connector (C).Carefully put the wires back into the outlet box.


4. Attach the ceiling pan of the fixture to the mounting strap unit (A) by inserting the threaded pipe, then secure it with the finial (D).
5. Install 3 X 60W Max. medium base bulbs (not included).
See relamping label at socket area or packaging for maximum wattage allowed.

Turn on the power at fuse or circuit box.




The following parts are available for reorder if damaged or missing.

Spare Parts List:



Mounting Strap Unit (A) Mounting Screw (B) Wire Connector (C) Finial (D)

Assembly Kit
7250MM (1 SET)



A: 6-1/2"
B: 13-1/4"

1 Year Warranty

Vaxcel warrants all of our products against defects in workmanship and finishes for one year following the date of shipment.

Exclusions: This warranty does not include the failure of products from extreme acts of nature; environmental conditions not suited for the products intended use; operation in temperatures outside of the range specified in the instruction manual; usage with improper power supply, power surges or dips. For coastal locations, some corrosion is considered normal for the environment.

Vaxcel reserves the right to repair, replace or issue a credit for any properly installed product, provided it is returned per RMA instruction. This warranty is limited to the cost of the product only and does not extend to transportation, installation or replacement costs.

How can warranty service be obtained?
info@vaxcel.com
1-800-482-9235