



DGDv1



DGD-SELECT

Models Available

DGD2 | 2-inch
DGD3 | 3-inch
DGD4 | 4-inch

DGD2 | 2-inch
DGD3 | 3-inch
DGD4 | 4-inch

Finishes



Voltage

120VAC

120VAC

Brightness

DGD2 | 356-384 Lm
DGD3 | 571-616 Lm
DGD4 | 983-1060 Lm

DGD2 | 428-507 Lm
DGD3 | 566-721 Lm
DGD4 | 784-1044 Lm

Efficiency

DGD2 | 74-80 Lm/W
DGD3 | 72-78 Lm/W
DGD4 | 84-91 Lm/W

DGD2 | 89-107 Lm/W
DGD3 | 71-90 Lm/W
DGD4 | 69-90 Lm/W

Color Temperature

Single CCT Models



cct select



Light Quality

DGD2 | 90 CRI (>50 R9)
DGD3 | 93 CRI (>50 R9)
DGD4 | 92 CRI (>50 R9)

DGD2 | 95 CRI (65 R9)
DGD3 | 93 CRI (57 R9)
DGD4 | 96 CRI (72 R9)

Adjustability

32° Tilt + 360° Rotation

32° Tilt + 360° Rotation

Beam Spread

DGD2 | 41°
DGD3 | 39°
DGD4 | 43°

DGD2 | 45°
DGD3 | 45°
DGD4 | 35°

Dimming

TRIAC, Down to 5%

TRIAC, Down to 10%

Listings & Certifications

