



FEATURES & BENEFITS

Design & Application

Versatile and practical lighting solution for various fire rated locations such as dwellings, corridors, and stairwells.

Durable steel housing ensures long-lasting performance and resistance to fire hazards.

Easy installation with adjustable spring-loaded retention tabs, allowing for a secure fit in ceilings up to 3/4" thick without the need for a recessed housing.

Precision Optics

Easy installation with adjustable spring-loaded retention tabs, allowing for a secure fit in ceilings up to 3/4" thick without the need for a recessed housing.

High Color Rendering Index (CRI) of 90+ ensures accurate and vibrant color representation, enhancing the visual appeal of the illuminated space.

Precision engineered optical stack optimizes the performance of the light source, delivering exceptional clarity and minimizing glare.

High Performance LED technology

Extended LED lifespan of over 72,000 hours (L70(9k)) minimizes maintenance needs and replacement costs.

Off-board driver design enhances heat management, maximizing the longevity of the fixture.

Dimmable functionality allows for easy control of light levels, creating the desired atmosphere or adjusting to different lighting requirements.

Increased ROI

Dimmable functionality allows for easy control of light levels, creating the desired atmosphere or adjusting to different lighting requirements.

Compliance with industry standards and certifications ensures reliable performance, reducing the risk of product failure and associated costs.

Compliance with ENERGYSTAR standards ensures energy-efficient operation, resulting in reduced electricity bills and environmental impact.

Environmentally Friendly

RoHS compliant, ensuring the use of environmentally safe materials that are free from hazardous substances.

Title 24 compliant, meeting stringent energy efficiency regulations and promoting sustainable practices.

Certified for direct contact with insulation (IC-Rated) to promote energy efficiency by preventing air leaks and heat loss, reducing the need for additional insulation.

Installation Versatility

Accompanied by a remote driver/junction box with multiple KOs and poke-in connectors, allowing for flexible installation options.

Wet location rating (cETLus 1598 Classified) enables installation in areas prone to moisture or humidity, expanding application possibilities.

Compliant with NFPA and NEC standards for closet use, ensuring safety and compliance in specific installation environments.

Flexible Control

Dimmable to 5% using compatible leading edge (TRIAC) or trailing edge (ELV) dimmers, offering easy control over light intensity.

Adjustable CCT selection (2700K, 3000K, 3500K, 4000K, and 5000K) allows users to customize the lighting ambiance to match their preferences or specific requirements.

Warranty coverage of 5 years provides peace of mind, guaranteeing the quality and longevity of the lighting system.

