



EXL1



EXL1-SELECT

Red or Green text options available

SELECTABILITY

Field selectable Red and Green light and lettering



Injection molded thermoplastic ABS housing

White Finishes

UL-94V-0 flame rating - Flame Retardant

Red or Green text options available

6" Letter Height

Single or Double Face Configuration

CONSTRUCTION

Injection molded thermoplastic ABS housing

White & Black Finishes Available

UL-94V-0 flame rating - Flame Retardant

Field Selectable Red and Green LED light and lettering

6" Letter Height

Single or Double Face Configuration

120/277V Dual Voltage Operation

LED Indicator Light & Push Button Test Switch

90 Min capacity on emergency mode

Damp Location Rated

Operating temperature rating of 32°F to 104°F (0°-40° C)

ELECTRICAL

120/277V dual voltage operation

LED indicator light & push-button test switch

90 Min capacity on emergency mode

Damp location rated

Operating temperature rating of 32°F to 104°F (0°-40°c)

Self-diagnostic testing automatically performs required monthly and annual test.

Input Voltage (V): 120/277VAC

Input Power (W): 3.8W

Charging Time: 24 hrs

Emergency Battery Run Time: 90 minutes

System Warranty: Year Limited

OTHERS

Input Voltage (V): 120/277VAC

Input Power (W): 1.2W


Charging Time: 24 hrs

Emergency Battery Run Time: 90 minutes

System Warranty: 1 Year Limited



CERTIFICATIONS



DIMENSIONS

