

1407

RAPID REPAIR WOOD ADHESIVE

**For Quick Repairs, Hollow Spots and Installing
Thresholds, Moldings and Medallions**



Powered by Microban® for superior
mold and mildew protection.

1. DESCRIPTION

ROBERTS® 1407 RAPID REPAIR WOOD ADHESIVE is a high solids, advanced acrylic latex adhesive designed for the installation of engineered and parquet wood flooring. This convenient tube size makes it easy for quick repairs and simple molding and trim installations.

Features and Benefits

- Advanced acrylic latex with 83% solids
- For glue assist when installing engineered wood, wood baseboards and parquet floors
- Ideal for quick repairs, hollow spots and installing thresholds, moldings and medallions
- Low odor and low VOC
- Coverage (per 30-oz. cartridge): 1/4" bead - 56 lineal feet
3/8" bead - 35 lineal feet
- Commercial and residential use
- Powered by Microban® for superior mold and mildew protection

Approved Flooring Types

Engineered wood

Wood baseboards

Moldings

Parquet floors

Approved Substrates

APA-rated plywood

Concrete (on or above grade)

Cork Underlayment (fully secured)

*For floorings and backings not listed, contact Technical Services at
(706) 277-5294 (U.S.A) and (905) 791-4444 (CA).*

2. TECHNICAL DATA

Product Type:	Advanced Acrylic Latex
Color:	Beige
Odor:	Very mild, non-offensive
Open Time:	Up to 20 minutes
Working Time:	Up to 30 minutes
Curing Time:	8 to 10 hours. Environmental factors and substrate porosity effect cure rate. Restrict foot traffic and moving of heavy objects for 24 hours to allow adhesive to cure properly. Premature traffic can cause installation failure.
Traffic:	Residential: 24 hours Commercial: 24 hours Rolling Loads: N/A
pH:	Must not exceed 9
Shelf Life:	2 years from date of manufacture when stored in the original unopened container in a controlled environment 50°F - 77°F (10°C - 25°C)
Storage:	Protect from freezing
VOC:	< 2 g/L



**SHELF LIFE
2 YEARS**

3. INSTRUCTIONS

Limitations

- For interior installations only
- Not recommended over non-porous materials or painted surfaces
- Concrete and plaster must be properly seasoned and dry prior to installation

Preparation

Surface must be structurally sound, dry, smooth, level and free all substances (oil, wax, grease, paint, oil based sealers, adhesive residue, etc.) that may inhibit the bond of the adhesive or the performance or its installation.

Installation

Maintain the same temperature and humidity during the life of the installation (between 65–95°F).

Stair treads – Apply 1/4" bead in a zig-zag pattern.

Moldings – Size of the bead and amount of bead rows will depend upon molding size.

Reducer strips – Apply 1/8" bead to substrate and allow up to 15 min. open time and then install strip.

Starter/endrows – Apply 1/4" bead along the entire back of plank. Surface conditions and type of wood product will ultimately determine bead size and coverage.

Clean-up

Fresh adhesive – warm, soapy water

Dried adhesive – mineral spirits sparingly on a clean, cotton cloth.

DO NOT POUR DIRECTLY ONTO FLOORING.

4. AVAILABILITY



USA

30 Oz Tube	1407-30C	075378140702
------------	----------	--------------



Canada

887 mL Tube	1407RB852	075378140702
-------------	-----------	--------------



5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications.

Visit robertsconsolidated.com, robertsconsolidated.com/ca or call (866) 435-8665 for full warranty details.

6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A. / (905) 791-4444 Canada.



**made in
USA**

ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc.
LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

E2428-01372



Roberts Consolidated Industries, Inc.
300 Cross Plains Blvd, Dalton, GA 30721
Customer Service: (866) 435-8665
Technical Support: (706) 277-5294
robertsconsolidated.com



Roberts Company Canada, Ltd.
34 Hansen Road, Brampton, ON L6W 3H4
Customer Service: (866) 435-8665
Technical Support: (905) 791-4444
robertsconsolidated.com/ca

a quality brand of
QEP