

NICOR®

VT5

COMPARISON SHEET



	VT3-20		VT4	VT5
INPUT VOLTAGE	120-277VAC		120-277VAC	120-277VAC
CCT OPTIONS	Single CCT Only: 4000K or 5000K		Selectable: 3.5K 4K 5K	Selectable: 3.5K 4K 5K
WATTAGE OPTIONS	Standard Output (4S) 38W	High Output (4H) 52W	Selectable: 34W 38W 45W	2FT Selectable: 17W, 21W, 26W 4FT Selectable: 34W, 40W, 46W 6FT Selectable: 52W, 68W, 80W
LENGTHS OFFERED	2 Ft, 4 Ft, 8 Ft		4 Ft	2 Ft, 4 Ft, 8 Ft
DELIVERED LUMENS	4,952 - 4,992 Lm	6,724 - 6,778	5364 - 7964 Lm	2,555 – 12,245 Lm
SYSTEM EFFICACY	130 Lm/W	130 Lm/W	134 - 152 Lm/W	146.7 – 164.1 Lm/W
DLC	DLC 5.1 Standard		DLC 5.1 Standard	DLC 6.0 Premium
LENS	Wrapped Polycarbonate		Wrapped Polycarbonate	Wrapped, Frosted Polycarbonate
12V ACCESSORY PORT	Not Available		12VDC Accessory Port	12V Sensor Output
DIMMING	0-10VDC (down to 10%)		0-10VDC (Dim-to-Off)	0-10VDC (Dim-to-Off)
OPERATING TEMPERATURE	-40°F to 122°F (-40°C to 50°C)		Surface Mounted: -40°F to 113°F (-40°C to 45°C) Suspended: -40°F to 122°F (-40°C to 50°C)*	Surface Mounted: -40°F to 113°F (-40°C to 45°C) Suspended: -40°F to 122°F (-40°C to 50°C)
MOTION SENSOR	Not Available		Microwave Sensor Available	Internal or External Microwave/PIR Sensor Available
MOUNTING OPTIONS	Surface Mount and Suspension Cable Mount		Surface Mount and Suspension Cable Mount	Surface Mount and Suspension Cable Mount
BATTERY BACKUP	8W and 16W Options*		8W and 18W Options	4W, 8W, and 18W Options
WARRANTY	5-Year Limited		5-Year Limited	5-Year Limited
CERTIFICATIONS	   		    	    

* Emergency pack only available on 4' and 8' versions.

* When suspended at least 18" from ceiling.