



## PS699

### TRANSITIONAL PRESSURE SENSITIVE ADHESIVE

#### 1. PRODUCT NAME

Capitol® PS699 PRESSURE SENSITIVE ADHESIVE

#### 2. MANUFACTURER

Capitol® Flooring Products  
Dalton, GA 30720  
www.capitolflooringproducts.com  
866-435-8665

#### 3. DESCRIPTION

**Capitol® PS699** Transitional Pressure-Sensitive Adhesive is a very aggressive, high-tack transitional adhesive that installs like a pressure-sensitive adhesive but firms as it cures to form a permanent bond. Capitol PS699 combines features of both permanent and releasable adhesives, making it suitable for different installation needs across a wide array of resilient and carpet floor coverings. Capitol PS699 offers superior shear strength, excellent plasticizer, pH and moisture resistance (99% RH / 12 lbs MVER) to withstand extreme environmental conditions and will perform under heavy rolling loads and in all traffic conditions. VOC: <1 g/L.

#### Features and Benefits

- Compatible with a wide range of resilient and carpet tiles
- Flexible installation methods – Wet Set and Pressure Sensitive
- Maximum moisture tolerance of 99% RH / 12lb MVER
- Superior shear strength
- Ideal for environments with heavy traffic or rolling loads
- Durability with reduced floor movement
- Easy to use and easy to clean
- Apply with a trowel or roller
- Spreads opaque white and dries clear
- Includes green tracers
- AMP Guard®, antimicrobial product
- FloorScore and CRI Certified

PS699 is a solvent free, acrylic polymer blend adhesive that meets the strict requirements of the South Coast Air Quality Management District and may contribute one LEED point for “Low-Emitting Material–Adhesive and Sealant” (IEQ Credit 4.1) and “Low-Emitting Materials–Flooring Systems” (IEQ Credit 4.3). This product may also contribute to LEED points for MR Credit 5. Visit usgbc.org for additional details.

#### USES

For adhering LVP, LVT, VCT, vinyl-backed carpet tiles, vinyl sheet goods, rubber (tile and sheet), stair treads (rubber & vinyl), carpet cushion to substrate, cork-backed hard surface, cork flooring and cork underlayment.

#### Coverage and Trowel Options\*

##### POROUS SUBSTRATES:

##### 1/16" X 1/16" X 1/16" SQ-Notch

Flooring: LVP, LVT, VCT, vinyl sheet flooring, carpet tile, rubber sports flooring, natural cork and rubber underlayment  
Coverage: Up to 125-185 ft<sup>2</sup> per gallon

##### POROUS / NON-POROUS SUBSTRATES:

##### 1/16" x 1/32" x 1/32" U-Notch

LVP, LVT and cork underlayment  
Coverage: Up to 185-260 ft<sup>2</sup> per gallon

##### NON-PORPOUS SUBSTRATE:

LVP, LVT, VCT, carpet tile and cork underlayment  
3/8" Short Nap Roller  
Coverage: 250-350 ft<sup>2</sup> per gallon

*\*The trowel notches referenced are those typically recommended for the type of flooring being installed and are shown as a guide. Consult flooring manufacturer for their specific trowel recommendations.*



## PS699

### TRANSITIONAL PRESSURE SENSITIVE ADHESIVE

#### SUBSTRATES

Concrete, APA-rated plywood, Terrazzo, VCT (properly prepared), radiant-heated subfloors (surface temperature < 85F), sheet vinyl (properly prepared) excluding self-stick, association0-approved particle board, cork underlayment, OSB (oriented strand board), ceramic tile (properly prepared), cement backerboard (primed), and Gypsum (primed).

For floorings and backings not listed, contact Technical Services at (706) 277-5294.

#### LIMITATIONS

- For interior controlled environments only.
- Not intended for use as a moisture mitigation system, see flooring manufacturer for any RH limitations for their respected products. Do not install in areas with known hydrostatic moisture problems or pH imbalances (pH tolerance 6-12).

#### 4. TECHNICAL DATA

<b>Product Type:</b>	Acrylic Polymer Blend
<b>Color:</b>	Off-white with green tracers
<b>Odor:</b>	Very mild
<b>PERMANENT Installation (Wet-Set Method)</b>	
<b>Open Time:</b>	Up to 20 minutes
<b>Working Time:</b>	Up to 40 minutes
<b>PRESSURE SENSITIVE Installation (Full-Tack Method)</b>	
<b>Open Time:</b>	Up to 60 minutes
<b>Working Time:</b>	Up to 12 hours Setup time will vary slightly with temperature and porosity of substrate
<b>Curing Time:</b>	24-48 hours
<b>Traffic:</b>	Residential: 0 min (PSA) 12 hours (semi-wet)
<b>Commercial:</b>	4 hours
<b>Rolling Loads:</b>	24 hours
<b>pH:</b>	Must not exceed 12
<b>VOC:</b>	< 1 g/L
<b>Shelf Life:</b>	2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning.
<b>Storage:</b>	While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 20°F (-6.7°C)

#### 5. INSTRUCTION

##### PREPARATION

Concrete substrate must be dry (within tested moisture tolerance of flooring and adhesive product). Subfloors must be clean, structurally sound and within flat and level tolerance of manufacturer. All substrates must be free of substances such as paints, oils, epoxies, old adhesive residues, etc. that might inhibit the bond of the adhesive or the performance of the flooring or its installation. All substrate cracks, chips, holes, joints or high spots must be adequately repaired. Patching compounds must be suitable for the use application, cement-based and polymer-modified, and applied according to the manufacturer's instructions.

##### INSTALLATION

Maintain a consistent temperature and ambient relative humidity before, during and after installation (between 65-85°F and 30-50% ambient RH). Follow all industry standards and flooring manufacturer's recommendations for floor flatness, acclimation and application of flooring materials. Spread adhesive uniformly onto the substrate using a trowel (see trowel panel for recommendations). Adhesive trowel ridges should be well defined, consistent and achieve full coverage of the substrate. Observe appropriate open time.

**When installing over a porous substrate:** place flooring into semi-wet adhesive for a permanent bond or allow adhesive to dry and become tacky to the touch for a releasable bond.

**When installing over non-porous substrate:** always allow adhesive to completely dry and become tacky before placing flooring. Once adhesive field has reached appropriate tack, install the floor covering into the adhesive field.

Roll the floor covering with a weighted roller per manufacturer's specific guidelines.

Post installation: Restrict foot traffic and moving of heavy objects for 24 hours.

**CLEAN UP:** For best results, remove fresh adhesive immediately and completely with – warm, soapy water on a clean cloth. Dried Adhesive – mineral spirits sparingly on clean, cotton cloth. Do not pour directly onto the flooring.



# PS699



## TRANSITIONAL PRESSURE SENSITIVE ADHESIVE

### 6. AVAILABILITY

#### USA

Packaging PS699-4 (4-gal plastic pail 075378069942)

Packaging PS699-1 (1-gal plastic pail 075378069911)

#### Canada

Packaging PS699RB015 (4-gal plastic pail 024043000117)

### 7. WARRANTY

Capitol® offers a limited product warranty on this product when installed in accordance with the printed specifications. Ask your sales associate visit [www.capitolflooringproducts.com](http://www.capitolflooringproducts.com) or call (866) 435-8665 for a copy of the warranty.

### 8. MAINTENANCE

Not applicable.

### 9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at 706-277-5294 or visit [www.capitolflooringproducts.com](http://www.capitolflooringproducts.com).

### 10. FILING SYSTEM

Division 9

