




POWERPIPE X SERIES DATA SHEET



TECHNICAL SPECIFICATIONS

SKU	PPX12-M 60668 - Each
Woofers	12" (305mm) anodized aluminum cone, rubber surround, high excursion
Frequency Response	34Hz - 100Hz +/-3dB
Impedance	4 ohms nominal
Sensitivity (2.83V/1m)	93dB SPL
Enclosure	Marine-Grade Aluminum
Finish	Textured Black
Recommended Power	500 watts
Recommended Amplifiers	Blaze Powerzone Connect 1502 3004 6008 Sonance DSP 2-750 MKIII
Tube Inside Diameter	5.98" (152mm)
Tube Length	25.59" (650mm)
Product Dims w/ Feet (WxHxD)	14.59" x 15.2" x 15.3" (370.59mm x 386.08mm x 388.62mm)
Product Dims w/o Feet (WxHxD)	14.59" x 14.59" x 15.3" (370.59mm x 370.59mm x 388.62mm)
Product Weight	40.9 lbs. (18.55kg) Team lift required

ACCESSORIES

PPX-8R | 93796
PPX 8" XPC Grille Connector

PPX-6R | 93795
PPX 6" XPC Grille Connector

PPX-6-90 | 93793
PPX 90-Degree Adapter

PPX-3.5x16-2-STR | 93790
PPX Straight Toekick Connector and Grille

PPX-3.5x16-2-90 | 93789
PPX 90-Degree Toekick Connector and Grille

PPX TOEKICK REPLACEMENT GRILLE | 93799
Straight or 90-Degree Toekick Connector Required