

# Hybrid Driver & Type A LED Tube

(UL Type C System)



Project Name \_\_\_\_\_

Date \_\_\_\_\_ Type \_\_\_\_\_

Notes \_\_\_\_\_

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time.

Current's Type A LED tubes and hybrid drivers create a UL Type C system to maximize rebate potential. Current offers compatible 2', 3', and 4' tubes rated at 70,000 hours and a value 4' tube rated at 50,000 hours.

Drivers are non-dimmable and must be paired with the exact lamps listed below to qualify as UL Type C system. Electrical ratings for the 2-lamp and 4-lamp hybrid drivers:

Order Code	Driver Description	Input (V)	Max Input (W)	Max Input (A)	Output (V)	Max Output (W)	Output (A)	PF	THD	Frequency (Hz)
21418	LED-ET8/DR/2L	120-277	35	0.4	100-160	32	0.14-0.17x2	>0.9	<15	50/60
21506	LED-ET8/DR/4L	120-277	64	0.8	100-160	60	0.14-0.17x4	>0.9	<15	50/60

## Lamp performance with the 2-lamp driver for 2 lamps (2L) and one lamp (1L):

LED Lamp Product Information						21418 LED-ET8/DR/2L			
Base Type	Order Code	Lamp Description	DLC®	UL	Lamp Watts	Lumens per Lamp (2L)	System Watts (2L)	Lumens per Lamp (1L)	System Watts (1L)
G13	35775	LED8ET8/G/2/830	-	Yes	8.5	1300	21	1950	19
G13	35776	LED8ET8/G/2/835	-	Yes	8.5	1350	21	2150	19
G13	35778	LED8ET8/G/2/840	-	Yes	8.5	1400	21	2300	19
G13	35779	LED8ET8/G/2/850	-	Yes	8.5	1350	21	2200	19
G13	35783	LED11T8/G/3/830	-	Yes	10.5	1450	24	2200	21
G13	35784	LED11T8/G/3/835	-	Yes	10.5	1500	24	2250	21
G13	35788	LED11T8/G/3/840	-	Yes	10.5	1500	24	2300	21
G13	35789	LED11T8/G/3/850	-	Yes	10.5	1550	24	2300	21
G13	34277	LED10ET8/G/4/830	Yes	Yes	10	1500	23	2350	20
G13	34279	LED10ET8/G/4/835	Yes	Yes	10	1600	23	2650	20
G13	34280	LED10ET8/G/4/840	Yes	Yes	10	1700	23	2800	20
G13	34282	LED10ET8/G/4/850	Yes	Yes	10	1650	23	2700	20
G13	34283	LED14ET8/G/4/830	Yes	Yes	13	1950	30	2700	23
G13	34289	LED14ET8/G/4/835	Yes	Yes	13	2000	30	2700	23
G13	34291	LED14ET8/G/4/840	Yes	Yes	13	2050	30	2850	23
G13	34300	LED14ET8/G/4/850	Yes	Yes	13	2050	30	2850	23
G13	35790	LED15ET8/G/4/830	Yes	Yes	13.5	1950	23	2750	23
G13	35791	LED15ET8/G/4/835	Yes	Yes	13.5	2000	23	2800	23
G13	35793	LED15ET8/G/4/840	Yes	Yes	13.5	2100	30	2900	23
G13	35797	LED15ET8/G/4/850	Yes	Yes	13.5	2100	30	2900	23
G13	35798	LED15ET8/G/4/865	-	Yes	13.5	2100	30	2900	23

# Hybrid Driver & Type A LED Tube

(UL Type C System)

Spec Tables

Project Name \_\_\_\_\_

Date \_\_\_\_\_ Type \_\_\_\_\_

Notes \_\_\_\_\_

## Lamp performance with the 4-lamp driver for 4 lamps (4L) and three lamps (3L):

LED Lamp Product Information						21506 LED-ET8/DR/4L				
Base Type	Order Code	Lamp Description	DLC®	UL	Voltage	Lamp Watts	Lumens per Lamp (4L)	System Watts (4L)	Lumens per Lamp (3L)	System Watts (3L)
G13	35775	LED8ET8/G/2/830	-	Yes	120-277V	8.5	1300	41	1450	37
G13	35776	LED8ET8/G/2/835	-	Yes	120-277V	8.5	1300	41	1550	37
G13	35778	LED8ET8/G/2/840	-	Yes	120-277V	8.5	1400	41	1650	37
G13	35779	LED8ET8/G/2/850	-	Yes	120-277V	8.5	1350	41	1600	37
G13	35783	LED11T8/G/3/830	-	Yes	120-277V	10.5	1450	49	1600	43
G13	35784	LED11T8/G/3/835	-	Yes	120-277V	10.5	1500	49	1700	43
G13	35788	LED11T8/G/3/840	-	Yes	120-277V	10.5	1500	49	1700	43
G13	35789	LED11T8/G/3/850	-	Yes	120-277V	10.5	1550	49	1750	43
G13	34277	LED10ET8/G/4/830	Yes	Yes	120-277V	10	1500	47	1450	41
G13	34279	LED10ET8/G/4/835	Yes	Yes	120-277V	10	1600	47	1500	41
G13	34280	LED10ET8/G/4/840	Yes	Yes	120-277V	10	1700	47	1600	41
G13	34282	LED10ET8/G/4/850	Yes	Yes	120-277V	10	1650	47	1550	41
G13	34283	LED14ET8/G/4/830	Yes	Yes	120-277V	13	1900	58	2150	45
G13	34289	LED14ET8/G/4/835	Yes	Yes	120-277V	13	2000	58	2200	45
G13	34291	LED14ET8/G/4/840	Yes	Yes	120-277V	13	2050	58	2250	45
G13	34300	LED14ET8/G/4/850	Yes	Yes	120-277V	13	2050	58	2250	45
G13	35790	LED15ET8/G/4/830	Yes	Yes	120-277V	13.5	1950	60	2200	51
G13	35791	LED15ET8/G/4/835	Yes	Yes	120-277V	13.5	2000	60	2250	51
G13	35793	LED15ET8/G/4/840	Yes	Yes	120-277V	13.5	2050	60	2300	51
G13	35797	LED15ET8/G/4/850	Yes	Yes	120-277V	13.5	2050	60	2300	51
G13	35798	LED15ET8/G/4/865	-	Yes	120-277V	13.5	2050	60	2300	51