


versatile™ 4C Mailbox, 4CADD-08




COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
MAILBOX	MB1	3" H x 12" W x 15" D	8
OUTGOING MAIL	OM1	3" H x 12" W x 15" D	1
PARCEL	PL5	17" H x 12" W x 15" D	2

- Notes:**
- This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - At least one customer compartment shall be positioned less than 48" above finished floor (AFF).
 - No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - No patron (tenant) lock shall be positioned more than 67" AFF.
 - No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - The USPS Arrow lock shall be positioned 36"- 48" AFF.
 - This 4C mailbox can also be used for private applications.
 - The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILE™ 4C FRONT LOAD MAILBOX

 <p>5935 Corporate Drive • Manhattan, KS 66503 800.275.1747 • www.florencemailboxes.com</p>	MODEL 4CADD-08	REV D
	SCALE NONE	LAST REV DATE 4/14/26
	DRAWING NUMBER 4CADD-08CS	DRAWN BY RAK