



WEDGE X SERIES DATA SHEET

TECHNICAL SPECIFICATIONS

	WX48QT 60692 - Each	WX58QT 60693 - Each
SKU	60692 - Each	60693 - Each
Tweeter	0.75" (19mm) four titanium domes, ferrofluid-cooled, acoustic back chamber	0.75" (19mm) four titanium domes, ferrofluid-cooled, acoustic back chamber
Woofer	(2) 4" (102mm) aluminum cone, santoprene surround	(2) 5.25" (133mm) aluminum cone, santoprene surround
Dispersion Technology	Quadrature tweeter with cymatic diffuser	Quadrature tweeter with cymatic diffuser
Crossover Technology	2-way CDX crossover, adjustable boundary switch	2-way CDX crossover, adjustable boundary switch
Frequency Response	70Hz - 20Hz +/-3dB	60Hz - 20Hz +/-3dB
Impedance	4 ohms nominal	4 ohms nominal
Sensitivity (2.83V/1m)	86dB SPL	88dB SPL
Recommended Power	50 watts minimum; 100 watts maximum	50 watts minimum; 100 watts maximum
Environmental	Marine ready, weatherproof wire gland	Marine ready, weatherproof wire gland (standard, recessed wire terminal option available on WX58QT model only)
Grille	Perforated aluminum with grille clip retention	Perforated aluminum with grille clip retention
Mounting	Bracket included	Bracket included
Product Dims (WxHxD)	22" x 4.76" x 4.76" (558.8mm x 120.9mm x 120.9mm)	22" x 6.23" x 5.86" (558.8mm x 158.24mm x 148.84mm)
Build to Order (W)	Standard or custom width (seamless grille: up to 96")	Standard or custom width (seamless grille: up to 96")
Product Weight	8.4 lbs. (3.81kg)	10.94 lbs. (4.96kg)
Bracket Weight	1.2 lbs. (0.54kg)	1.48 lbs. (0.67kg)
Shipping Weight	16 lbs. (7.26kg)	22 lbs. (9.98kg)

