

# NICOR<sup>®</sup>

## Comparison GUIDE

### SIZE OPTIONS

### TRIM OPTIONS

COLOR

FINISH

TYPE

OPTICS

### LUMEN OUTPUT



































### CCT OPTIONS

### LUMENS PER WATT

### PRODUCT LIFE

### DIMMING

### SPECIFICATIONS

NEW CONSTRUCTION & RETROFIT			RETROFIT
			
<b>CDG</b>	<b>DDA</b>	<b>CDA</b>	<b>CLR</b>
  4 & 6 inches	  3 inches	    4, 6, 8 & 10 inches	  6 & 8 inches
White, Specular, Haze Smooth, Prismatic (4 inches) Down, Wall Wash Medium (36°-60°), Medium Narrow (22°-36°)	White, Black Smooth, Baffle Down, Adjustable, Wall Wash* Spot - Wide	White, Specular, Haze, Black, Wheat, Champagne Smooth, Flangeless, or with Flange Down, Wall Wash* Narrow - Wide	Aged Copper, Nickel, Black Smooth White Down Standard (87°-97°)
1055-3877 Lm	1200-2200 Lm	1200-9300 Lm	1058-3239 Lm
 27K · 30K · 35K · 40K · 50K 5CCT Select	 27K / 30K / 35K / 40K / 50K Dim to Warm	 27K / 30K / 35K / 40K / 50K Dim to Warm	 30K · 35K · 40K · 50K 4CCT Select
80-118 Lm/W	80-100 Lm/W	68-133 Lm/W	91-112 Lm/W
>50,000 hrs	>50,000 hrs	>50,000 hrs	>56,000 hrs
0-10V	Tri Dimming: TRIAC, ELV, 0-10V	Tri Dimming: TRIAC, ELV, 0-10V	0-10V
    	  	  	    

\* Wall Wash has fewer trim options.

1 Wet Location when used with lens. See spec sheet for more information.