

# LED Replacement Lamps

## A-Line General Purpose Lamps



Project Name \_\_\_\_\_

Date \_\_\_\_\_ Type \_\_\_\_\_

Notes \_\_\_\_\_

Current's ENERGY STAR® rated LED A-Line lamps are the perfect low energy, long life replacements for standard incandescent, halogen and CFL lamps. New ENERGY STAR® 2.0 standards require lamps to be more efficient (higher LPW), and lower the minimum life rating to 15,000 hours. Take advantage of the ENERGY STAR® rating and check for utility rebates in your area.

### PERFORMANCE HIGHLIGHTS:

A-Line General Purpose Lamps	
<b>Light Output Range:</b>	400-2155 Lumens
<b>CRI:</b>	80
<b>CCT:</b>	2700K, 3000K, 4000K & 5000K
<b>Input Voltage:</b>	120
<b>Efficiency:</b>	Up to 130 LPW
<b>Wattage:</b>	4W-19W
<b>Life:</b>	15,000 hours L70
<b>Temperature Rating:</b>	-20°C to 40°C
<b>Rating:</b>	Damp

### LIMITED WARRANTY

3 Years

### FEATURES:

- Halogen-like color
- Up to 15,000 hours rated life (L70)
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

### BENEFITS:

- **Energy + Cost Savings**  
For example, a 60-watt incandescent replacement lamp using 10 watts of energy and producing 800 lumens can save over \$82 in energy costs over the rated life of the lamp vs. a standard 840 lumen, 60-watt incandescent A19 based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

### LEARN MORE:

To learn more about saving money and energy, go to [www.gecurrent.com](http://www.gecurrent.com).

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

# LED Replacement Lamps

## A-Line General Purpose Lamps

### Spec Table

Project Name \_\_\_\_\_

Date \_\_\_\_\_ Type \_\_\_\_\_

Notes \_\_\_\_\_

Base Type	Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	# Location Rating	Additional Information	
<b>A-LINE GENERAL PURPOSE LAMPS</b>																	
A-19	E26	4.5	37669	LED5DAGCSW-2P 120	120	6	4.4	450	2700	80	40	15,000	Yes	★	Damp	All Glass, Clear, 2 pack	
	E26	6	69115	LED6DA19/827	120	6	4.4	480	2700	80	40	15,000	Yes	★	Damp	White, Omnidirectional	
	E26	6	69118	LED6DA19/830	120	6	4.4	480	3000	80	40	15,000	Yes	★	Damp	White, Omnidirectional	
	E26	6	69132	LED6DA19/840	120	6	4.4	480	4000	80	40	15,000	Yes	★	Damp	White, Omnidirectional	
	E26	6	69144	LED6DA19/850	120	6	4.4	480	5000	80	40	15,000	Yes	★	Damp	White, Omnidirectional	
	E26	7	37674	LED7DAGCSW-2P	120	6	4.4	800	2700	80	60	15,000	Yes	★	Damp	All Glass, Clear, 2 pack	
	E26	8	99192	LED8AG/DL/4PK 120	120	6	4.4	760	5000	80	60	15,000	No	-	Damp	All Glass, Frosted, 4 pack	
	E26	8	99190	LED8AG/SW/4PK 120	120	6	4.4	760	2700	80	60	15,000	No	-	Damp	All Glass, Frosted, 4 pack	
	E26	10	69117	LED10DA19/827	120	6	4.4	800	2700	80	60	15,000	Yes	★	Damp	White, Omnidirectional	
	E26	10	69119	LED10DA19/830	120	6	4.4	800	3000	80	60	15,000	Yes	★	Damp	White, Omnidirectional	
	E26	10	69133	LED10DA19/840	120	6	4.4	800	4000	80	60	15,000	Yes	★	Damp	White, Omnidirectional	
	E26	10	69146	LED10DA19/850	120	6	4.4	800	5000	80	60	15,000	Yes	★	Damp	White, Omnidirectional	
	GU24	10	38220	LED10DA19GU24827	120	6	4.4	800	2700	80	60	15,000	Yes	★	Damp	White, Omnidirectional	
A-21	E26	12	76037	LED12DA21/827	120	6	5.16	1100	2700	80	75	15,000	Yes	★	Damp	White, Omni, ES 2.0	
	E26	12	76041	LED12DA21/830	120	6	5.16	1100	3000	80	75	15,000	Yes	★	Damp	White, Omni, ES 2.0	
	E26	12	76045	LED12DA21/840	120	6	5.16	1100	4000	80	75	15,000	Yes	★	Damp	White, Omni, ES 2.0	
	E26	12	76102	LED12DA21/850	120	6	5.16	1100	5000	80	75	15,000	Yes	★	Damp	White, Omni, ES 2.0	
	E26	12	73404	LED12DA21/850FE	120	6	5.31	1100	5000	80	75	25,000	Yes	-	Enclosed	White, Enclosed, Omni	
	E26	12	73384	LED12DA21/830FE	120	6	5.31	1100	3000	80	75	25,000	Yes	-	Enclosed	White, Enclosed, Omni	
	E26	15	76038	LED15DA21/827	120	6	5.16	1600	2700	80	100	15,000	Yes	★	Damp	White, Omni, ES 2.0	
	E26	15	76043	LED15DA21/830	120	6	5.16	1600	3000	80	100	15,000	Yes	★	Damp	White, Omni, ES 2.0	
	E26	15	76060	LED15DA21/840	120	6	5.16	1600	4000	80	100	15,000	Yes	★	Damp	White, Omni, ES 2.0	
	E26	15	76117	LED15DA21/850	120	6	5.16	1600	5000	80	100	15,000	Yes	★	Damp	White, Omni, ES 2.0	
		GU24	15	46666	LED15DA21GU24827	120	6	5.43	1600	2700	80	100	15,000	Yes	-	Damp	White, Omnidirectional
	E26	4/13/07	38188	LED13A30/100/827	120	6	5.31	400/1400/840	2700	80	30/70/100	15,000	-	-	Damp	White, 3-Way	
E26	5/19/10	38563	LED19A50/150/827	120	6	5.31	650/2155/1300	2700	80	50/100/150	15,000	-	-	Damp	White, 3-Way		
<b>LED Bright Stik™</b>																	
E26	5.5	66256	LED5.5LS3/827	120	48	4.45	450	2700	80	40	15,000	-	★	Damp	Case = 16 3-Pack		
E26	5.5	75177	LED5LS3/850	120	48	4.45	450	5000	80	40	15,000	-	★	Damp	Case = 16 3-Pack		
E26	9	75184	LED9LS3/827	120	48	4.45	800	2700	80	60	15,000	-	★	Damp	Case = 16 3-Pack		
E26	9	75588	LED9LS3/850	120	48	4.45	800	5000	80	60	15,000	-	★	Damp	Case = 16 3-Pack		
E26	12	75590	LED12LS2/827	120	32	5.24	1100	2700	80	75	15,000	-	★	Damp	Case = 16 2-Pack		
E26	12	75591	LED12LS2/850	120	32	5.24	1100	5000	80	75	15,000	-	★	Damp	Case = 16 2-Pack		
E26	15	75593	LED15LS2/827	120	32	5.24	1600	2700	80	100	15,000	-	★	Damp	Case = 16 2-Pack		
E26	15	75644	LED15LS2/850	120	32	5.24	1600	5000	80	100	15,000	-	★	Damp	Case = 16 2-Pack		

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900