

MOISTURE BARRICADE 6-MIL POLYETHYLENE FILM

For use with vinyl, laminate, SPC, WPC
and engineered wood flooring

70-115
70-116
70-117
70-118

ADHESIVE STRIP


Seals out moisture at the seams to protect floors

PROTECTIVE

Class 1 moisture barrier
prevents subfloor moisture from
reaching the finished floor

COVERAGE

Roll unfolds to cover an extra large area.
See below for individual roll dimensions



made in
USA

SPECIFICATIONS

ITEM #	70-115	70-116	70-117	70-118
UNIT OF MEASURE	12 rolls per case	6 rolls per case	1 roll per case	1 roll per case
COVERAGE	120 sq. ft / roll 1140 sq. ft / per case	300 sq. ft. / roll 1800 sq. ft / per case	600 sq. ft / roll	1000 sq. ft / roll
WIDTH OF ROLL	10 ft. (120")	12 ft. (144")	12 ft. (144")	12 ft. (144")
LENGTH OF ROLL	12 ft. (144")	25 ft. (300")	50 ft. (600")	83.5 ft. (1,002")
THICKNESS	6 mil	6 mil	6 mil	6 mil
WEIGHT PER ROLL	2.7 lbs.	7.8 lbs.	15 lbs.	23lbs.
DIAMETER OF ROLL	2-1/4"	3-3/4"	4-1/2"	6-1/2"

Scan here for
PRODUCT
INFORMATION



ROBERTS® Moisture Barricade is designed for use with vinyl, laminate, SPC, WPC and engineered wood flooring to protect finished floors against moisture damage. Recommended by the National Wood Flooring Association (NWFA), this 6-mil thick polyethylene film is a Class-1 moisture barrier over concrete subfloors that protects and extends the life of your floors. Can also be used with standard underlayments as an additional layer of moisture protection.