NICOR®

VERSION COMPARISON

HBC LED High Bay



	HBC6	HBC5	HBC4
MODELS AVAILABLE	HBC6150SUS8(BK,WH) HBC6240SUS(BK,WH)	HBC5150SUS8(BK,WH) HBC5240SUS8(BK,WH) HBC5300SUS8(BK,WH)	HBC4100U(BK,WH)8, HBC4150U(BK,WH)8 HBC4200U(BK,WH)8, HBC4240U(BK,WH)8 HBC4300U(BK,WH)8, HBC4400U(BK,WH)8
WATTAGE SELECTABLE	Yes 100W/120W/150W 200W/220W/240W	Yes 100W/120W/150W 200W/220W/240W 240W/270W/300W	No 100W, 150W, 200W 240W, 300W, 400W
CCT SELECTABLE	Yes (3CCT) 3500K/4000K/5000K	Yes (3CCT) 3500K/4000K/5000K	No 4000K or 5000K
BEAM ANGLE SELECTABLE	Yes (3 angles) 60°/80°/100°	No 90°	No 88°
VOLTAGE INPUT	120-277VAC	120-277VAC 277-480VAC	120-277, 277-480VAC (on 150W+)
COLOR OPTIONS	Black, White	Black, White	Black, White
OPTICAL ACCESSORIES	Aluminum Reflector Polycarbonate Reflector Polycarbonate Glare Shield Wire Guard	Aluminum Reflector Polycarbonate Reflector Polycarbonate Glare Shield Wire Guard	Aluminum Reflector Polycarbonate Reflector Polycarbonate Glare Shield Wire Guard
MOUNTING ACCESSORIES	Pendant Adapter Yoke Mount	Pendant Adapter Yoke Mount	Pendant Adapter Yoke Mount
EMERGENCY PACK	EMB400v2 with Optional Remote	EMB400v2 with Optional Remote	EMB400v2 with Optional Remote
CONTROLS CAPABILITY	12VDC output lead, onboard sensor socket (PIR, MW, NLC)	12VDC output lead, onboard sensor socket (PIR, MW, NLC)	12VDC output lead, onboard sensor socket (PIR, MW, NLC)
DIMENSIONS	Diameter / Height 11.8″ 5.8″ (150W) 14.2″ 6.2″ (240W)	Diameter / Height 11.0″ 6.7″ (150W) 13.4″ 7.5″ (240W) 3.8″ 9.6″ (300W)	Diameter / Height 12.4″ 6.7″ (100-150W) 14.2″ 8.9″ (200-240W) 17.7″ 9.4″ (300-400W)
CERTIFICATIONS			