



OWR4

FEATURES & BENEFITS



1. Visual Aesthetic & Application

The clean, low-profile wall pack design provides a modern appearance while delivering uniform illumination through a ribbed lens that minimizes glare and hot spots. Selectable wattage and CCT allow a single fixture to adapt to a variety of perimeter, entryway, garage, tunnel, and general commercial lighting applications. The durable UV- and fire-resistant construction is designed to withstand demanding outdoor environments.



2. Performance

Selectable wattage and color temperature provide installation flexibility while helping simplify inventory management. High efficacy, quality color rendering, and full-range 0-10V dimming deliver energy-efficient performance without compromising visual comfort. Universal voltage, an efficient driver, and an optional emergency battery backup ensure dependable operation across a variety of applications.



3. Controls

A factory-installed photocell automatically turns the fixture on at dusk and off at dawn to maximize energy savings. The photocell can be disabled in the field when alternative lighting controls are preferred. Full-range 0-10V dimming provides additional flexibility for lighting control strategies.



4. Installation

Direct mounting to a standard 4/O J-Box allows for fast and straightforward installation with minimal effort. The fixture secures directly to the junction box using screws, simplifying both new construction and retrofit projects. Surge protection recommendations help improve long-term system reliability in areas susceptible to electrical disturbances.



5. Certifications and Listings

Recognized industry certifications verify the fixture's safety, energy efficiency, and durability for outdoor commercial applications. Wet location and IP65 ratings provide confidence in reliable performance when exposed to the elements. Long-life testing and a 5-year limited warranty support dependable operation and long-term value.