

BLACK JACK®

FLOATING FLOOR CUSHION UNDERLAYMENT

Underlayment for floating laminate, bamboo and engineered wood floors

70-026
70-026-XL



PROTECTION

Includes adhesive strip for easy installation and 3" overlap to seal out moisture

COMFORT

2.5 mm thick foam provides optimal floor cushion

MOLD DEFENSE

Dense structure offers mold and mildew protection

LONG LASTING

Anti-crush technology for shock absorption and long life

THERMAL INSULATION

Ideal for radiant-heated floors



IIC	STC	Δ IIC	R-Value
70	66	21	0.425



MOISTURE VAPOR
RESISTANT



MOLD & MILDEW
DEFENSE



SOUND
CONTROL



RADIANT
HEAT



CUSHIONING
& LEVELING

IIC and STC tests measure sound transference from an upper level room to a lower level room. The IIC measures sound such as moving furniture and walking, while the STC measures sound such as voices and television. International Building Code requires a minimum 50 for IIC and STC. Δ Delta Rating is the only true measurement of sound reduction from a product (not a floor assembly) in the industry.

Black Jack® Floating Floor Cushion Underlayment is a dense foam underlayment that helps absorb everyday in-room noise under floating laminate, bamboo and engineered flooring.

The 2.5 mm thick foam layer provides optimal cushioning and sound absorption, and ideal for use with radiant-heated floors. The closed-cell design provides excellent moisture vapor resistance, and helps fight mold and mildew. For added convenience and time savings, Black Jack features a 3" overlap and adhesive strip to join pieces and help seal out moisture.

Scan here for
PRODUCT
INFORMATION



SPECIFICATIONS

ITEM #	70-026	70-026-XL
UNIT OF MEASURE	12 rolls / case	2 rolls / case
COVERAGE	100 sq. ft. / roll 1200 sq. ft. / case	600 sq. ft. / roll 1200 sq. ft. / case
WIDTH OF ROLL	43"	43"
LENGTH OF ROLL	28 ft.	167.5 ft.
THICKNESS	2.5 mm	2.5 mm
WEIGHT PER ROLL	1.95 lbs.	11 lbs.
DIAMETER OF ROLL	6.75"	16"