

MSC

Cylindrical Wall Sconce

Product Description

The MSC Cylindrical Wall Sconce embodies sophistication with a minimalist approach. This ADA-compliant wall sconce features thin cylindrical shades that emit a warm glow when lit, adding a touch of elegance to any indoor space. Crafted from durable die-formed cold-rolled steel, this hardwired sconce is perfect for corridors, bedrooms, or any indoor areas where style and function are paramount.

Construction

- Die-formed cold-rolled steel
- High transmission acrylic diffuser for uniform light distribution
- Integrated LED
- Fixture Dimension (WxHxD) : 4.3" x 11.2" x 3.6"
- Hardwired fixture; professional installation recommended

Maintenance

- Wipe with a soft cloth
- No abrasive cleaners

Electrical

- Input Voltage: 120-277VAC
- Input Wattage: 9W

Mounting and installation

- Easy installation on a recessed junction box
- Fixture mounts directly to J-Boxes with mounting plate and threaded nipple
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

Listings

- cETLus listed
- Damp locations
- ADA Compliant

Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)

Photometric Data

MSC - 3000K

Input Voltage (VAC)	120-277
System Level Power (W)	9
Delivered Lumens (Lm)	700
System Efficacy (Lm/W)	77.7
Correlated Color Temp (K)	3000
Color Rendering Index (CRI)	>80

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Ordering Information

Example: MSC1UNV308NK

Series	Version	Voltage	Light Source	CCT	CRI	Finish
MSC	1	UNV (120-277)	LED (Integrated)	30 (3000K)	8 (>80)	NK (Nickel)
						OB (Oiled Bronze) ¹
						BK (Black) ¹

Specifications and dimensions subject to change without notice. Please refer to the website for the most up-to-date information.

1. Contact factory for MOQ and lead times on OB and BK finishes.

NICOR LLC 2200 Midtown Place NE, Albuquerque, NM 87107 P: 800.821.6283 F: 800.892.8393
www.nicorlighting.com April 1, 2025 4:29 PM MSC Page 1

Project _____

Catalog _____

Type _____

Date _____

