



# 3000

## MULTIPURPOSE

### Residential & Commercial Carpet and Felt-Backed Sheet Vinyl



Powered by Microban® for superior mold and mildew protection.

#### 1. DESCRIPTION

ROBERTS® 3000 MULTIPURPOSE is a contract-grade adhesive formulated for the installation of most types of commercial carpet and felt-backed sheet vinyl. Formulated with a longer open time for optimal positioning of felt-backed vinyl flooring, plus develop stack for the installation of rigid-backed carpet.

#### Features and Benefits

- Versatile low-odor, low-VOC formula
- Longer open time for optimal positioning
- Moisture control up to 5 lbs. MVER and 80% RH
- Coverage up to 180 ft<sup>2</sup>/gal
- Commercial and residential use
- Powered by Microban® for superior mold and mildew protection

#### Approved Flooring Types

Commercial carpet

Residential carpet

Felt-backed sheet vinyl

#### Backings (smooth back & rough back)

Unitary

Actionbac®

Jute

Polypropylene

Polyurethane

#### Approved Substrates

Concrete

APA-rated plywood

OSB (oriented strand board) lightly sanded

Terrazzo

For floorings and backings not listed, contact Technical Services at (706) 277-5294 (U.S.A.).

#### Recommended Trowel and Coverage Rate\*

##### 1/8" x 1/8" x 1/16" (3 mm x 3 mm x 1.5 mm) Flat-Top V Notch

Flooring (porous substrate): Carpet Backings: (Polypropylene)

Coverage: 90-110 ft<sup>2</sup>/per gallon (8.3-10.2 m<sup>2</sup>/per 3.78 L)

##### 1/16" x 1/16" x 1/16" (1.5 mm x 1.5 mm x 1.5 mm) SQ Notch

Flooring (porous substrate): Carpet Backings: (Closed Cell & Enhancer)

Coverage: 65-75 ft<sup>2</sup>/per gallon (6-6.9 m<sup>2</sup>/per 3.78 L)

##### 1/16" x 1/16" x 3/32" (1.5 mm x 1.5 mm x 2.3 mm) U Notch

Flooring (porous substrate): Felt-Backed Sheet Vinyl

Coverage: 160-180 ft<sup>2</sup>/per gallon (14.8-16.7 m<sup>2</sup>/per 3.78 L)



SHELF LIFE  
**2 YEARS**



LIFETIME  
**WARRANTY\***

\*Based on installation by an industry certified installer

## 2. TECHNICAL DATA

<b>Product Type:</b>	SBR Latex
<b>Color:</b>	Tan
<b>Odor:</b>	Very mild, non-offensive
<b>Open Time:</b>	Up to 60 minutes
<b>Working Time:</b>	Up to 90 minutes <i>Setup time will vary slightly with temperature and porosity of substrate</i>
<b>Curing Time:</b>	24 hours
<b>Traffic:</b>	Residential: 12 hours Commercial: 24 hours Rolling Loads: N/A
<b>MVER:</b>	5 lbs or less (ASTM F1869) / 80% RH or less (ASTM F2170)
<b>pH:</b>	Must not exceed 9
<b>Shelf Life:</b>	2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning
<b>Storage:</b>	Protect from freezing
<b>VOC:</b>	<1 g/L

## 3. INSTRUCTIONS

### Limitations

- For interior installations only
- Do not use this adhesive for pure vinyl or vinyl-backed product

### Preparation

Subfloors must be structurally sound, dry, smooth, at ( $\leq 3/16"$  within 10'), level and free of excess moisture/alkali and all contaminants (oil, debris, paint, sealers, adhesive residue, etc.) that may inhibit the bond of the adhesive or the performance of the flooring and its installation. All substrate cracks, chips, holes, joints, high spots and irregularities must be adequately repaired. Patching compounds must be suitable for the use application, cement-based and polymer-modified, and applied according to the manufacturer's instructions.

### Installation

Materials and area temperature must be between 65–95°F with a maximum RH of 65% for 48 hours, before and during installation, as well as for 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation. Lift a corner periodically to ensure 100% coverage of adhesive to the floor backing and the substrate to ensure a void-free bond. Spread adhesive uniformly. Adhesive ridges should be of sufficient height to achieve full coverage of the substrate and the back of the flooring. Place flooring into the adhesive while the adhesive is still fresh.

### Clean-up

*Fresh adhesive* – warm, soapy water on a clean cloth.

*Dried adhesive* – use mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR DIRECTLY ONTO FLOORING.**

## 4. AVAILABILITY

USA**		
4 G Plastic Pail	3000-4	075378300045
1 G Plastic Pail	3000-1	075378300014



## 5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. **Lifetime Warranty applies only for installations performed by industry certified professional installers.**

Visit [robertsconsolidated.com](http://robertsconsolidated.com) or call (866) 435-8665 for full warranty details.

## 6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company

\*\* Note: Only product manufactured in the USA is FloorScore Certified

Y0125-00136



**Roberts Consolidated Industries, Inc.**  
300 Cross Plains Blvd, Dalton, GA 30721  
Customer Service: (866) 435-8665  
Technical Support: (706) 277-5294  
[robertsconsolidated.com](http://robertsconsolidated.com)

