

TROWELS AT A GLANCE

FOR CARPET, VINYL SHEET, LVT, VCT & WOOD

Notch Size	Application	D-Handle (11" Blade)	Wood Handle (11" Blade)	Economy
1/16" x 1/16" x 1/16" SQ	For carpet tile, fiberglass sheet, felt-backed sheet, luxury vinyl tile, plank, and cork underlayment	49605*		10-181-16*
1/16" x 1/16" x 1/16" SQ	For carpet tile, fiberglass sheet, felt-backed sheet, luxury vinyl tile and plank	49601*	10-810 (with 10° blade angle)	
1/8" x 1/8" x 1/8" SQ	For pre-finished parquet and wall base	49602*		
1/8" x 1/8" x 1/8" U	For residential and commercial carpet	49604*		
1/8" x 1/8" x 1/16" Flat-Top V	For secondary-backed carpet, direct glue-down, sheet vinyl installations, and cork underlayment	49604*		10137-12
1/16" x 1/32" x 1/32" U	For VCT, vinyl, luxury vinyl tile and plank	49601*		10-181-16*
1/16" x 1/32" x 5/64" U	For carpet tile, fiberglass sheet, felt-backed sheet, and VCT		49738	
1/4" x 1/4" x 1/4" SQ	For thinset application of ceramic tile 8" x 8" or smaller, laminated wood plank flooring, flat milled solid & shorts or plywood		49713 (QEP)	10113 (QEP) 49915 (QEP)
1/4" x 1/4" x 1/4" Flat-Top V	For pre-finished engineered wood plank, solid wood, bamboo and acrylic impregnated plank flooring	49602*		
1/4" x 3/16" Tiger Tooth®	For bamboo, solid and engineered wood flooring up to 1/2 in. thick	49603*		
3/16" x 1/4" x 1/2" Flat-Top V	For laminated wood plank, solid wood, bamboo and acrylic impregnated plank flooring	49603*		
3/32" x 3/32" x 3/32" Flat-Top V	For residential and commercial carpet	49605*		

Always check adhesive/mortar manufacturer's trowel recommendations before selecting a trowel notch.

All trowels measure: width x depth x space apart.

Recommended notch sizes by NTCA (National Tile Contractors Association)

* Double Sided Trowels

